

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Sertra 100mgSTSH4B00
User ID :	pm98770	Batch NO. :	SHM2501410
Print Interval :	50000 Tablets	Running Time :	00 Hour 46 Min 24 Sec
Total Counter :	200212	Total Running Time :	1048 Hour 6 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	26	%	Manual ;	15	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		3000000	Tablets			
Air Pressure Low Limit :		0.500	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		45	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	21.07	kN	No		
HEP :	25.0 %	20.26	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	16.53	kN	Yes 10	Times	
Ref :		16.21	kN			
LCP :	2.0 %	15.88	kN	Yes 10	Times	
LEP :	25.0 %	12.15	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	11.34	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	4.52	kN	Min :	4.43	kN	Punch NO.;	13
SD :	1.00	%	Max :	4.69	kN	Punch NO.;	35
Mean Main Pressure :	16.05	kN	Min :	15.37	kN	Punch NO.;	13
SD :	2.60	%	Max :	17.65	kN	Punch NO.;	3
Filling Depth :	Increase ;	19	Times	Decrease ;	9	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	7	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	5.60	mm	Pre Thickness ;	3.10	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	4.53	mm	Main Thickness ;	2.03	mm
Filling Depth :	8.05	mm	Current Cam :	Cam C	
Main Air pressure :	0.767	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	11	Min			
Lower Punch Remain Time (S2):	2	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.29	kN		
	Max ;	0.42	kN	Max Punch ;	58
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.12	kN	Max Punch ;	37
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.09	kN	Max Punch ;	1

Tablet Data (N/A)

Total Counter :	200212	Tablets			
A.W.C Counter :	197787	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	197787 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Sertra 100mgSTSH4B00
User ID :	pm98770	Batch NO. :	SHM2501410
Print Interval :	50000 Tablets	Running Time :	00 Hour 46 Min 24 Sec
Total Counter :	200212	Total Running Time :	1048 Hour 6 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	25	%	Manual ;	15	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		3000000	Tablets			
Air Pressure Low Limit :		0.500	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		45	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	21.01	kN	No		
HEP :	25.0 %	20.21	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	16.49	kN	Yes 10	Times	
Ref :		16.16	kN			
LCP :	2.0 %	15.84	kN	Yes 10	Times	
LEP :	25.0 %	12.12	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	11.32	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	4.61	kN	Min :	4.49	kN	Punch NO.;	24
SD :	1.10	%	Max :	4.75	kN	Punch NO.;	36
Mean Main Pressure :	16.28	kN	Min :	15.39	kN	Punch NO.;	19
SD :	3.40	%	Max :	18.11	kN	Punch NO.;	3
Filling Depth :	Increase ; 29	Times	Decrease ;	15	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	7	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	5.60	mm	Pre Thickness ;	3.10	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	4.64	mm	Main Thickness ;	2.14	mm
Filling Depth :	7.79	mm	Current Cam :	Cam C	
Main Air pressure :	0.767	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	11	Min			
Lower Punch Remain Time (S2):	2	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.29	kN		
	Max ;	0.42	kN	Max Punch ;	58
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.12	kN	Max Punch ;	36
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.09	kN	Max Punch ;	1

Tablet Data (N/A)

Total Counter :	200212	Tablets			
A.W.C Counter :	197787	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	197787 (100.0%)	Tablets			