

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Sertra 100mgSTSH4B00
User ID :	rp98927	Batch NO. :	SHM2501410
Print Interval :	50000 Tablets	Running Time :	10 Hour 48 Min 28 Sec
Total Counter :	2801644	Total Running Time :	1058 Hour 10 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	26	%	Manual ;	15	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		3000000	Tablets			
Air Pressure Low Limit :		0.500	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		45	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	21.54	kN	No		
HEP :	25.0 %	20.71	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	16.90	kN	Yes 10	Times	
Ref :		16.57	kN			
LCP :	2.0 %	16.24	kN	Yes 10	Times	
LEP :	25.0 %	12.43	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	11.60	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	4.47	kN	Min :	4.38	kN	Punch NO.;	27
SD :	0.90	%	Max :	4.61	kN	Punch NO.;	35
Mean Main Pressure :	16.49	kN	Min :	15.67	kN	Punch NO.;	70
SD :	2.20	%	Max :	17.81	kN	Punch NO.;	35
Filling Depth :	Increase ; 82	Times	Decrease ; 78	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	7	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	5.60	mm	Pre Thickness ;	3.10	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	4.53	mm	Main Thickness ;	2.03	mm
Filling Depth :	8.07	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.778	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	40	Min			
Lower Punch Remain Time (S2):	4	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.26	kN		
	Max ;	0.41	kN	Max Punch ;	58
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.14	kN	Max Punch ;	74
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.06	kN	Max Punch ;	77

Tablet Data (N/A)

Total Counter :	2801644	Tablets			
A.W.C Counter :	2797853	Tablets			
HEP :	2 (0.0%)	Tablets	LEP :	319 (0.0%)	Tablets
GOOD :	2797532 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Sertra 100mgSTSH4B00
User ID :	rp98927	Batch NO. :	SHM2501410
Print Interval :	50000 Tablets	Running Time :	10 Hour 48 Min 28 Sec
Total Counter :	2801644	Total Running Time :	1058 Hour 10 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	25	%	Manual ;	15	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		3000000	Tablets			
Air Pressure Low Limit :		0.500	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		45	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	21.76	kN	No		
HEP :	25.0 %	20.92	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	17.07	kN	Yes 10	Times	
Ref :		16.74	kN			
LCP :	2.0 %	16.40	kN	Yes 10	Times	
LEP :	25.0 %	12.55	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	11.72	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	4.55	kN	Min :	4.45	kN	Punch NO.;	17
SD :	1.00	%	Max :	4.67	kN	Punch NO.;	20
Mean Main Pressure :	16.63	kN	Min :	15.37	kN	Punch NO.;	32
SD :	3.20	%	Max :	18.25	kN	Punch NO.;	75
Filling Depth :	Increase ;	130	Times	Decrease ;	123	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	7	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	5.60	mm	Pre Thickness ;	3.10	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	4.64	mm	Main Thickness ;	2.14	mm
Filling Depth :	7.80	mm	Current Cam :	Cam C	
Main Air pressure :	0.778	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	40	Min			
Lower Punch Remain Time (S2):	4	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.25	kN		
	Max ;	0.40	kN	Max Punch ;	57
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.14	kN	Max Punch ;	74
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.06	kN	Max Punch ;	77

Tablet Data (N/A)

Total Counter :	2801644	Tablets			
A.W.C Counter :	2797930	Tablets			
HEP :	2 (0.0%)	Tablets	LEP :	319 (0.0%)	Tablets
GOOD :	2797609 (100.0%)	Tablets			