

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	pb97604	Batch NO. :	EWM2507750
Print Interval :	50000 Tablets	Running Time :	00 Hour 16 Min 55 Sec
Total Counter :	50036	Total Running Time :	1059 Hour 10 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	108	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		45	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	26.53	kN	No		
HEP :	25.0 %	25.51	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	20.82	kN	Yes 10	Times	
Ref :		20.41	kN			
LCP :	2.0 %	20.00	kN	Yes 10	Times	
LEP :	25.0 %	15.31	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	14.29	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	4.62	kN	Min :	4.44	kN	Punch NO.;	33
SD :	2.00	%	Max :	4.96	kN	Punch NO.;	43
Mean Main Pressure :	20.39	kN	Min :	19.33	kN	Punch NO.;	29
SD :	3.20	%	Max :	22.57	kN	Punch NO.;	13
Filling Depth :	Increase ;	9	Times	Decrease ;	12	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	30	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	6.35	mm	Pre Thickness ;	3.35	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.40	mm	Main Thickness ;	2.40	mm
Filling Depth :	7.86	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.777	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	32	Min			
Lower Punch Remain Time (S2):	11	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.15	kN		
	Max ;	0.20	kN	Max Punch ;	30
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.14	kN	Max Punch ;	12
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.05	kN	Max Punch ;	6

Tablet Data (N/A)

Total Counter :	50036	Tablets			
A.W.C Counter :	43132	Tablets			
HEP :	2 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	43130 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	pb97604	Batch NO. :	EWM2507750
Print Interval :	50000 Tablets	Running Time :	00 Hour 16 Min 55 Sec
Total Counter :	50036	Total Running Time :	1059 Hour 10 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	108	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		45	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	25.84	kN	No		
HEP :	25.0 %	24.85	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	20.28	kN	Yes	10 Times	
Ref :		19.88	kN			
LCP :	2.0 %	19.48	kN	Yes	10 Times	
LEP :	25.0 %	14.91	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	13.91	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	4.62	kN	Min :	4.38	kN	Punch NO.;	33
SD :	2.50	%	Max :	4.97	kN	Punch NO.;	43
Mean Main Pressure :	19.56	kN	Min :	18.47	kN	Punch NO.;	46
SD :	3.50	%	Max :	21.32	kN	Punch NO.;	13
Filling Depth :	Increase ;	21	Times	Decrease ;	13	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	30	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	6.30	mm	Pre Thickness ;	3.30	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.42	mm	Main Thickness ;	2.42	mm
Filling Depth :	7.57	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.777	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	32	Min			
Lower Punch Remain Time (S2):	11	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.15	kN		
	Max ;	0.21	kN	Max Punch ;	30
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.14	kN	Max Punch ;	12
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.05	kN	Max Punch ;	6

Tablet Data (N/A)

Total Counter :	50036	Tablets			
A.W.C Counter :	43132	Tablets			
HEP :	2 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	43130 (100.0%)	Tablets			