

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	pm98770	Batch NO. :	EWM2507750
Print Interval :	50000 Tablets	Running Time :	11 Hour 09 Min 09 Sec
Total Counter :	1989410	Total Running Time :	1070 Hour 2 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	50	%	Manual ;	15	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		45	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	27.97	kN	No		
HEP :	25.0 %	26.89	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	21.95	kN	Yes 10	Times	
Ref :		21.52	kN			
LCP :	2.0 %	21.09	kN	Yes 10	Times	
LEP :	25.0 %	16.14	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	15.06	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	4.73	kN	Min :	4.58	kN	Punch NO.;	25
SD :	1.80	%	Max :	5.02	kN	Punch NO.;	45
Mean Main Pressure :	21.32	kN	Min :	19.50	kN	Punch NO.;	46
SD :	3.40	%	Max :	23.35	kN	Punch NO.;	35
Filling Depth :	Increase ;	49	Times	Decrease ;	57	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.35	mm	Pre Thickness ;	3.36	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.40	mm	Main Thickness ;	2.41	mm
Filling Depth :	7.75	mm	Current Cam :	Cam C	
Main Air pressure :	0.796	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	18	Min			
Lower Punch Remain Time (S2):	13	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.18	kN		
	Max ;	0.25	kN	Max Punch ;	36
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.11	kN	Max Punch ;	2
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.08	kN	Max Punch ;	18

Tablet Data (N/A)

Total Counter :	1989410	Tablets			
A.W.C Counter :	1981025	Tablets			
HEP :	29 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	1980996 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	pm98770	Batch NO. :	EWM2507750
Print Interval :	50000 Tablets	Running Time :	11 Hour 09 Min 09 Sec
Total Counter :	1989410	Total Running Time :	1070 Hour 2 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	50	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		45	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	27.47	kN	No		
HEP :	25.0 %	26.42	kN	Yes	10	Rotations 10 Tablets
HCP :	2.0 %	21.56	kN	Yes	10	Times
Ref :		21.13	kN			
LCP :	2.0 %	20.71	kN	Yes	10	Times
LEP :	25.0 %	15.85	kN	Yes	10	Rotations 10 Tablets
LSP :	30.0 %	14.79	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	4.72	kN	Min :	4.50	kN	Punch NO.;	33
SD :	2.10	%	Max :	4.99	kN	Punch NO.;	43
Mean Main Pressure :	21.32	kN	Min :	19.56	kN	Punch NO.;	46
SD :	4.00	%	Max :	23.46	kN	Punch NO.;	13
Filling Depth :	Increase ;	31	Times	Decrease ;	34	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.30	mm	Pre Thickness ;	3.31	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.42	mm	Main Thickness ;	2.43	mm
Filling Depth :	7.55	mm	Current Cam :	Cam C	
Main Air pressure :	0.796	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	18	Min			
Lower Punch Remain Time (S2):	13	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.18	kN		
	Max ;	0.23	kN	Max Punch ;	30
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.11	kN	Max Punch ;	2
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.08	kN	Max Punch ;	18

Tablet Data (N/A)

Total Counter :	1989410	Tablets			
A.W.C Counter :	1981025	Tablets			
HEP :	29 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	1980996 (100.0%)	Tablets			