

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	pr190041	Batch NO. :	EWM2507750
Print Interval :	50000 Tablets	Running Time :	16 Hour 07 Min 07 Sec
Total Counter :	2875766	Total Running Time :	1075 Hour 0 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	50	%	Manual ;	15	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		10	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	28.08	kN	No		
HEP :	25.0 %	27.00	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	22.03	kN	Yes 10	Times	
Ref :		21.60	kN			
LCP :	2.0 %	21.16	kN	Yes 10	Times	
LEP :	25.0 %	16.20	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	15.12	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	4.89	kN	Min :	4.67	kN	Punch NO.;	26
SD :	2.30	%	Max :	5.18	kN	Punch NO.;	53
Mean Main Pressure :	21.65	kN	Min :	20.56	kN	Punch NO.;	29
SD :	3.30	%	Max :	23.49	kN	Punch NO.;	14
Filling Depth :	Increase ; 12	Times	Decrease ;	15	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.35	mm	Pre Thickness ;	3.36	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.40	mm	Main Thickness ;	2.41	mm
Filling Depth :	7.88	mm	Current Cam :	Cam C	
Main Air pressure :	0.818	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	26	Min			
Lower Punch Remain Time (S2):	2	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.20	kN		
	Max ;	0.27	kN	Max Punch ;	30
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.11	kN	Max Punch ;	27
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.04	kN	Max Punch ;	46

Tablet Data (N/A)

Total Counter :	2875766	Tablets			
A.W.C Counter :	2864968	Tablets			
HEP :	98 (0.0%)	Tablets	LEP :	250 (0.0%)	Tablets
GOOD :	2864620 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	pr190041	Batch NO. :	EWM2507750
Print Interval :	50000 Tablets	Running Time :	16 Hour 07 Min 07 Sec
Total Counter :	2875766	Total Running Time :	1075 Hour 0 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	50	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		10	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	28.38	kN	No		
HEP :	25.0 %	27.29	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	22.27	kN	Yes	10 Times	
Ref :		21.83	kN			
LCP :	2.0 %	21.39	kN	Yes	10 Times	
LEP :	25.0 %	16.37	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	15.28	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	4.86	kN	Min :	4.66	kN	Punch NO.;	42
SD :	2.00	%	Max :	5.08	kN	Punch NO.;	52
Mean Main Pressure :	21.93	kN	Min :	20.05	kN	Punch NO.;	29
SD :	4.00	%	Max :	24.18	kN	Punch NO.;	14
Filling Depth :	Increase ;	4	Times	Decrease ;	4	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.30	mm	Pre Thickness ;	3.31	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.40	mm	Main Thickness ;	2.41	mm
Filling Depth :	7.61	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.818	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	26	Min			
Lower Punch Remain Time (S2):	2	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.20	kN		
	Max ;	0.27	kN	Max Punch ;	30
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.11	kN	Max Punch ;	49
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.20	kN	Max Punch ;	19

Tablet Data (N/A)

Total Counter :	2875766	Tablets			
A.W.C Counter :	2864968	Tablets			
HEP :	98 (0.0%)	Tablets	LEP :	250 (0.0%)	Tablets
GOOD :	2864620 (100.0%)	Tablets			