

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	yd98913	Batch NO. :	EWM2507850
Print Interval :	50000 Tablets	Running Time :	01 Hour 07 Min 23 Sec
Total Counter :	200052	Total Running Time :	1085 Hour 11 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	50	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		10	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	26.33	kN	No		
HEP :	25.0 %	25.32	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	20.66	kN	Yes	10 Times	
Ref :		20.26	kN			
LCP :	2.0 %	19.85	kN	Yes	10 Times	
LEP :	25.0 %	15.19	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	14.18	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	5.33	kN	Min :	5.10	kN	Punch NO.;	33
		2.40	%	Max :	5.69	kN	Punch NO.;	1
Mean Main Pressure :	SD :	22.49	kN	Min :	21.01	kN	Punch NO.;	46
		3.00	%	Max :	24.21	kN	Punch NO.;	13
Filling Depth :	Increase ;	137	Times	Decrease ;	98	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.35	mm	Pre Thickness ;	3.36	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.40	mm	Main Thickness ;	2.41	mm
Filling Depth :	8.54	mm	Current Cam :	Cam C	
Main Air pressure :	0.775	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	26	Min			
Lower Punch Remain Time (S2):	2	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.16	kN		
	Max ;	0.25	kN	Max Punch ;	31
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.12	kN	Max Punch ;	5
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.21	kN	Max Punch ;	52

Tablet Data (N/A)

Total Counter :	200052	Tablets			
A.W.C Counter :	196850	Tablets			
HEP :	51 (0.0%)	Tablets	LEP :	78 (0.0%)	Tablets
GOOD :	196721 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	yd98913	Batch NO. :	EWM2507850
Print Interval :	50000 Tablets	Running Time :	01 Hour 07 Min 23 Sec
Total Counter :	200052	Total Running Time :	1085 Hour 11 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	50	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		10	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	25.91	kN	No		
HEP :	25.0 %	24.91	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	20.33	kN	Yes	10 Times	
Ref :		19.93	kN			
LCP :	2.0 %	19.53	kN	Yes	10 Times	
LEP :	25.0 %	14.95	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	13.95	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	4.75	kN	Min :	4.47	kN	Punch NO.;	33
SD :	2.60	%	Max :	5.05	kN	Punch NO.;	43
Mean Main Pressure :	20.07	kN	Min :	19.01	kN	Punch NO.;	15
SD :	3.90	%	Max :	22.28	kN	Punch NO.;	13
Filling Depth :	Increase ;	112	Times	Decrease ;	106	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.30	mm	Pre Thickness ;	3.31	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.40	mm	Main Thickness ;	2.41	mm
Filling Depth :	7.79	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.775	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	26	Min			
Lower Punch Remain Time (S2):	2	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.16	kN		
	Max ;	0.22	kN	Max Punch ;	31
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.12	kN	Max Punch ;	5
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.21	kN	Max Punch ;	52

Tablet Data (N/A)

Total Counter :	200052	Tablets			
A.W.C Counter :	196850	Tablets			
HEP :	51 (0.0%)	Tablets	LEP :	78 (0.0%)	Tablets
GOOD :	196721 (99.9%)	Tablets			