

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	pm98770	Batch NO. :	EWM2507850
Print Interval :	50000 Tablets	Running Time :	10 Hour 22 Min 48 Sec
Total Counter :	1850932	Total Running Time :	1094 Hour 27 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	50	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		18	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	26.94	kN	No		
HEP :	25.0 %	25.90	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	21.13	kN	Yes	10 Times	
Ref :		20.72	kN			
LCP :	2.0 %	20.31	kN	Yes	10 Times	
LEP :	25.0 %	15.54	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	14.50	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	4.59	kN	Min :	4.29	kN	Punch NO.;	48
SD :	2.00	%	Max :	4.80	kN	Punch NO.;	22
Mean Main Pressure :	20.53	kN	Min :	19.36	kN	Punch NO.;	8
SD :	2.60	%	Max :	21.91	kN	Punch NO.;	13
Filling Depth :	Increase ;	244	Times	Decrease ;	219	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.35	mm	Pre Thickness ;	3.36	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.40	mm	Main Thickness ;	2.41	mm
Filling Depth :	8.08	mm	Current Cam :	Cam C	
Main Air pressure :	0.706	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	6	Min			
Lower Punch Remain Time (S2):	14	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.21	kN		
	Max ;	0.28	kN	Max Punch ;	32
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.10	kN	Max Punch ;	39
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.05	kN	Max Punch ;	38

Tablet Data (N/A)

Total Counter :	1850932	Tablets			
A.W.C Counter :	1845781	Tablets			
HEP :	152 (0.0%)	Tablets	LEP :	456 (0.0%)	Tablets
GOOD :	1845173 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	pm98770	Batch NO. :	EWM2507850
Print Interval :	50000 Tablets	Running Time :	10 Hour 22 Min 48 Sec
Total Counter :	1850932	Total Running Time :	1094 Hour 27 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	50	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		18	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	27.01	kN	No		
HEP :	25.0 %	25.97	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	21.20	kN	Yes 10	Times	
Ref :		20.78	kN			
LCP :	2.0 %	20.36	kN	Yes 10	Times	
LEP :	25.0 %	15.58	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	14.55	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	4.59	kN	Min :	4.41	kN	Punch NO.;	33
SD :	2.10	%	Max :	4.82	kN	Punch NO.;	53
Mean Main Pressure :	20.77	kN	Min :	19.47	kN	Punch NO.;	29
SD :	3.70	%	Max :	23.57	kN	Punch NO.;	13
Filling Depth :	Increase ;	238	Times	Decrease ;	238	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.30	mm	Pre Thickness ;	3.31	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.40	mm	Main Thickness ;	2.41	mm
Filling Depth :	7.76	mm	Current Cam :	Cam C	
Main Air pressure :	0.706	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	6	Min			
Lower Punch Remain Time (S2):	14	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.21	kN		
	Max ;	0.28	kN	Max Punch ;	32
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.09	kN	Max Punch ;	3
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.15	kN	Max Punch ;	20

Tablet Data (N/A)

Total Counter :	1850932	Tablets			
A.W.C Counter :	1845781	Tablets			
HEP :	152 (0.0%)	Tablets	LEP :	456 (0.0%)	Tablets
GOOD :	1845173 (100.0%)	Tablets			