

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	pb97604	Batch NO. :	EWM2507850
Print Interval :	50000 Tablets	Running Time :	18 Hour 51 Min 13 Sec
Total Counter :	3363650	Total Running Time :	1102 Hour 55 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	55	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		18	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	27.37	kN	No		
HEP :	25.0 %	26.31	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	21.47	kN	Yes	10 Times	
Ref :		21.05	kN			
LCP :	2.0 %	20.63	kN	Yes	10 Times	
LEP :	25.0 %	15.79	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	14.74	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	4.62	kN	Min :	4.43	kN	Punch NO.;	15
SD :	1.80	%	Max :	4.82	kN	Punch NO.;	52
Mean Main Pressure :	20.75	kN	Min :	19.48	kN	Punch NO.;	46
SD :	2.80	%	Max :	22.35	kN	Punch NO.;	12
Filling Depth :	Increase ;	41	Times	Decrease ;	62	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	15	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.35	mm	Pre Thickness ;	3.36	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.40	mm	Main Thickness ;	2.41	mm
Filling Depth :	8.43	mm	Current Cam :	Cam C	
Main Air pressure :	0.706	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	42	Min			
Lower Punch Remain Time (S2):	18	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.19	kN		
	Max ;	0.26	kN	Max Punch ;	30
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.15	kN	Max Punch ;	12
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.07	kN	Max Punch ;	52

Tablet Data (N/A)

Total Counter :	3363650	Tablets			
A.W.C Counter :	3357242	Tablets			
HEP :	169 (0.0%)	Tablets	LEP :	1012 (0.0%)	Tablets
GOOD :	3356061 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	pb97604	Batch NO. :	EWM2507850
Print Interval :	50000 Tablets	Running Time :	18 Hour 51 Min 13 Sec
Total Counter :	3363650	Total Running Time :	1102 Hour 55 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	54	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		18	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	27.01	kN	No		
HEP :	25.0 %	25.97	kN	Yes	10	Rotations 10 Tablets
HCP :	2.0 %	21.20	kN	Yes	10	Times
Ref :		20.78	kN			
LCP :	2.0 %	20.36	kN	Yes	10	Times
LEP :	25.0 %	15.58	kN	Yes	10	Rotations 10 Tablets
LSP :	30.0 %	14.55	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	4.57	kN	Min :	4.35	kN	Punch NO.;	37
SD :	2.20	%	Max :	4.81	kN	Punch NO.;	53
Mean Main Pressure :	20.55	kN	Min :	19.48	kN	Punch NO.;	15
SD :	3.80	%	Max :	22.69	kN	Punch NO.;	13
Filling Depth :	Increase ;	38	Times	Decrease ;	26	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	15	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.30	mm	Pre Thickness ;	3.31	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.40	mm	Main Thickness ;	2.41	mm
Filling Depth :	7.94	mm	Current Cam :	Cam C	
Main Air pressure :	0.706	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	42	Min			
Lower Punch Remain Time (S2):	18	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.19	kN		
	Max ;	0.26	kN	Max Punch ;	30
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.15	kN	Max Punch ;	12
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.04	kN	Max Punch ;	16

Tablet Data (N/A)

Total Counter :	3363650	Tablets			
A.W.C Counter :	3357242	Tablets			
HEP :	169 (0.0%)	Tablets	LEP :	1012 (0.0%)	Tablets
GOOD :	3356061 (100.0%)	Tablets			