

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	pb97604	Batch NO. :	EWM2507850
Print Interval :	50000 Tablets	Running Time :	20 Hour 15 Min 17 Sec
Total Counter :	3613806	Total Running Time :	1104 Hour 19 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	55	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		18	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	26.86	kN	No		
HEP :	25.0 %	25.83	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	21.08	kN	Yes	10 Times	
Ref :		20.66	kN			
LCP :	2.0 %	20.25	kN	Yes	10 Times	
LEP :	25.0 %	15.50	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	14.46	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	4.51	kN	Min :	4.30	kN	Punch NO.;	36
SD :	2.10	%	Max :	4.74	kN	Punch NO.;	1
Mean Main Pressure :	20.09	kN	Min :	19.16	kN	Punch NO.;	46
SD :	2.90	%	Max :	21.76	kN	Punch NO.;	14
Filling Depth :	Increase ;	63	Times	Decrease ;	104	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	15	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.35	mm	Pre Thickness ;	3.36	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.40	mm	Main Thickness ;	2.41	mm
Filling Depth :	7.96	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.823	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	21	Min			
Lower Punch Remain Time (S2):	9	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.20	kN		
	Max ;	0.26	kN	Max Punch ;	32
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.13	kN	Max Punch ;	51
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.20	kN	Max Punch ;	53

Tablet Data (N/A)

Total Counter :	3613806	Tablets			
A.W.C Counter :	3606647	Tablets			
HEP :	174 (0.0%)	Tablets	LEP :	1104 (0.0%)	Tablets
GOOD :	3605369 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	pb97604	Batch NO. :	EWM2507850
Print Interval :	50000 Tablets	Running Time :	20 Hour 15 Min 17 Sec
Total Counter :	3613806	Total Running Time :	1104 Hour 19 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	54	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		18	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	27.01	kN	No		
HEP :	25.0 %	25.97	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	21.20	kN	Yes	10 Times	
Ref :		20.78	kN			
LCP :	2.0 %	20.36	kN	Yes	10 Times	
LEP :	25.0 %	15.58	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	14.55	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	4.61	kN	Min :	4.44	kN	Punch NO.;	13
SD :	2.00	%	Max :	4.86	kN	Punch NO.;	53
Mean Main Pressure :	20.69	kN	Min :	19.11	kN	Punch NO.;	29
SD :	3.90	%	Max :	23.05	kN	Punch NO.;	13
Filling Depth :	Increase ;	63	Times	Decrease ;	58	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	15	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.30	mm	Pre Thickness ;	3.31	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.40	mm	Main Thickness ;	2.41	mm
Filling Depth :	7.76	mm	Current Cam :	Cam C	
Main Air pressure :	0.823	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	21	Min			
Lower Punch Remain Time (S2):	9	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.20	kN		
	Max ;	0.27	kN	Max Punch ;	43
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.13	kN	Max Punch ;	51
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.20	kN	Max Punch ;	53

Tablet Data (N/A)

Total Counter :	3613806	Tablets			
A.W.C Counter :	3606700	Tablets			
HEP :	174 (0.0%)	Tablets	LEP :	1104 (0.0%)	Tablets
GOOD :	3605422 (100.0%)	Tablets			