

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	sj97904	Batch NO. :	EWM2507850
Print Interval :	50000 Tablets	Running Time :	00 Hour 27 Min 28 Sec
Total Counter :	4364274	Total Running Time :	1108 Hour 32 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	54	%	Manual ;	15	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		18	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	27.62	kN	No		
HEP :	25.0 %	26.56	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	21.67	kN	Yes 10	Times	
Ref :		21.25	kN			
LCP :	2.0 %	20.82	kN	Yes 10	Times	
LEP :	25.0 %	15.93	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	14.87	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	4.66	kN	Min :	4.44	kN	Punch NO.;	33
SD :	1.90	%	Max :	4.85	kN	Punch NO.;	45
Mean Main Pressure :	20.72	kN	Min :	19.76	kN	Punch NO.;	43
SD :	2.80	%	Max :	22.50	kN	Punch NO.;	14
Filling Depth :	Increase ; 201	Times	Decrease ;	235	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	15	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.35	mm	Pre Thickness ;	3.36	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.40	mm	Main Thickness ;	2.41	mm
Filling Depth :	8.19	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.822	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	16	Min			
Lower Punch Remain Time (S2):	16	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.20	kN		
	Max ;	0.27	kN	Max Punch ;	30
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.12	kN	Max Punch ;	23
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.19	kN	Max Punch ;	21

Tablet Data (N/A)

Total Counter :	4364274	Tablets			
A.W.C Counter :	4354942	Tablets			
HEP :	317 (0.0%)	Tablets	LEP :	1184 (0.0%)	Tablets
GOOD :	4353441 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	sj97904	Batch NO. :	EWM2507850
Print Interval :	50000 Tablets	Running Time :	00 Hour 27 Min 28 Sec
Total Counter :	4364274	Total Running Time :	1108 Hour 32 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	54	%	Manual ;	15	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		18	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	27.53	kN	No		
HEP :	25.0 %	26.47	kN	Yes	10	Rotations 10 Tablets
HCP :	2.0 %	21.60	kN	Yes	10	Times
Ref :		21.17	kN			
LCP :	2.0 %	20.75	kN	Yes	10	Times
LEP :	25.0 %	15.88	kN	Yes	10	Rotations 10 Tablets
LSP :	30.0 %	14.82	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	4.75	kN	Min :	4.56	kN	Punch NO.;	36
SD :	2.10	%	Max :	5.00	kN	Punch NO.;	1
Mean Main Pressure :	21.38	kN	Min :	19.81	kN	Punch NO.;	46
SD :	3.30	%	Max :	23.05	kN	Punch NO.;	12
Filling Depth :	Increase ;	141	Times	Decrease ;	125	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	15	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.30	mm	Pre Thickness ;	3.31	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.40	mm	Main Thickness ;	2.41	mm
Filling Depth :	7.83	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.822	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	16	Min			
Lower Punch Remain Time (S2):	16	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.20	kN		
	Max ;	0.27	kN	Max Punch ;	29
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.12	kN	Max Punch ;	23
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.19	kN	Max Punch ;	21

Tablet Data (N/A)

Total Counter :	4364274	Tablets			
A.W.C Counter :	4354942	Tablets			
HEP :	317 (0.0%)	Tablets	LEP :	1184 (0.0%)	Tablets
GOOD :	4353441 (100.0%)	Tablets			