

## PRODUCTION REPORT

### Product Information

|                  |               |                      |                        |
|------------------|---------------|----------------------|------------------------|
| Machine Name :   | VANTIX P720D  | Product Name :       | MET 500<br>MG,STEW1A00 |
| User ID :        | am98755       | Batch NO. :          | EWM2507950             |
| Print Interval : | 50000 Tablets | Running Time :       | 00 Hour 42 Min 51 Sec  |
| Total Counter :  | 102090        | Total Running Time : | 1109 Hour 56 Min       |
| Station :        | Station 1     |                      |                        |

### Setting Value

|                                    |             |                   |         |                    |              |           |
|------------------------------------|-------------|-------------------|---------|--------------------|--------------|-----------|
| Feeder :                           | Auto ;      | 65                | %       | Manual ;           | 15           | RPM       |
| Filling Cam :                      |             | Cam B<br>4.5-10mm |         | Cam Range :        | Min :        | 2.50 mm   |
| Target Quantity :                  |             | 4500000           | Tablets |                    | Max :        | 8.00 mm   |
| Air Pressure Low Limit :           |             | 0.400             | MPa     |                    |              |           |
| Oil Lubrication :                  |             |                   |         |                    |              |           |
| Upper Punch Interval Time(S1) ;    |             | 45                | Min     | Supply Time ;      | 1.0          | Sec       |
| Lower Punch Interval Time(S2) ;    |             | 18                | Min     | Supply Time ;      | 3.0          | Sec       |
| Powder Supply Time :               |             | 5.0               | Sec     |                    |              |           |
| Initial Reject Time :              |             | 2                 | Tablets |                    |              |           |
| Upper Punch Tightness High Limit : |             | 1.00              | kN      |                    |              |           |
| Lower Punch Tightness High Limit : |             | 4.00              | kN      |                    |              |           |
| Ejecting Force High Limit :        |             | 4.00              | kN      |                    |              |           |
|                                    |             |                   |         | Stop Condition ;   |              |           |
| HSP :                              | 30.0 %      | 14.00             | kN      | No                 |              |           |
| HEP :                              | 25.0 %      | 13.46             | kN      | Yes 10             | Rotations 15 | Tablets   |
| HCP :                              | 2.0 %       | 10.99             | kN      | Yes 15             | Times        |           |
| Ref :                              |             | 10.77             | kN      |                    |              |           |
| LCP :                              | 2.0 %       | 10.56             | kN      | Yes 15             | Times        |           |
| LEP :                              | 25.0 %      | 8.08              | kN      | Yes 10             | Rotations 15 | Tablets   |
| LSP :                              | 30.0 %      | 7.54              | kN      | No                 |              |           |
| SD limit :                         | 35.0 %      |                   |         | Yes                |              |           |
| Pre HSP                            |             | 30.00             | kN      | Yes                |              |           |
| Mean Calculation range :           | 2 Rotations |                   |         | Calculation Pass : | 2            | Rotations |
| Empty Punch No. :                  | None        |                   |         |                    |              |           |

### Pressure Data

|                      |               |       |               |       |    |            |    |
|----------------------|---------------|-------|---------------|-------|----|------------|----|
| Mean Pre Pressure :  | 3.18          | kN    | Min :         | 2.90  | kN | Punch NO.; | 26 |
| SD :                 | 3.30          | %     | Max :         | 3.39  | kN | Punch NO.; | 36 |
| Mean Main Pressure : | 10.57         | kN    | Min :         | 9.32  | kN | Punch NO.; | 41 |
| SD :                 | 5.40          | %     | Max :         | 12.24 | kN | Punch NO.; | 21 |
| Filling Depth :      | Increase ; 26 | Times | Decrease ; 22 | Times |    |            |    |

## PRODUCTION REPORT

### Operation Value

|                               |         |     |                  |          |              |
|-------------------------------|---------|-----|------------------|----------|--------------|
| Disk Speed :                  | 22      | RPM | Capacity :       | 139920   | Tablets/hour |
| Feeder : Status ;             | Auto    |     | Speed ;          | 14       | RPM          |
| Pre Upper Punch Position ;    | 2.00    | mm  |                  |          |              |
| Pre Lower Punch Position ;    | 5.45    | mm  | Pre Thickness ;  | 3.45     | mm           |
| Main Upper Punch Position ;   | 2.00    | mm  |                  |          |              |
| Main Lower Punch Position ;   | 4.05    | mm  | Main Thickness ; | 2.05     | mm           |
| Filling Depth :               | 6.81    | mm  | Current Cam :    | Cam B    |              |
| Main Air pressure :           | 0.823   | MPa |                  | 4.5-10mm |              |
| Oil Lubrication status :      |         |     |                  |          |              |
| Upper Punch Remain Time (S1): | 32      | Min |                  |          |              |
| Lower Punch Remain Time (S2): | 15      | Min |                  |          |              |
| Lower Head Remain Time (S3):  | 0       | Min |                  |          |              |
| Powder Status :               | Disable |     | Dust Collector : | Off      |              |
| Initial Reject :              | Off     |     | Buzzer :         | Off      |              |

### Tightness

|                  |           |      |    |             |    |
|------------------|-----------|------|----|-------------|----|
| Upper Punch :    | Average ; | 0.00 | kN |             |    |
|                  | Max ;     | 0.04 | kN | Max Punch ; | 17 |
| Lower Punch :    | Average ; | 0.08 | kN |             |    |
|                  | Max ;     | 0.16 | kN | Max Punch ; | 7  |
| Ejection Force : | Average ; | 0.05 | kN |             |    |
|                  | Max ;     | 0.09 | kN | Max Punch ; | 19 |

### Tablet Data (N/A)

|                 |                   |         |       |        |         |
|-----------------|-------------------|---------|-------|--------|---------|
| Total Counter : | 102090            | Tablets |       |        |         |
| A.W.C Counter : | 89634             | Tablets |       |        |         |
| HEP :           | 11 (0.0%)         | Tablets | LEP : | 0 (0%) | Tablets |
| GOOD :          | 89623<br>(100.0%) | Tablets |       |        |         |

## PRODUCTION REPORT

### Product Information

|                  |               |                      |                        |
|------------------|---------------|----------------------|------------------------|
| Machine Name :   | VANTIX P720D  | Product Name :       | MET 500<br>MG,STEW1A00 |
| User ID :        | am98755       | Batch NO. :          | EWM2507950             |
| Print Interval : | 50000 Tablets | Running Time :       | 00 Hour 42 Min 51 Sec  |
| Total Counter :  | 102090        | Total Running Time : | 1109 Hour 56 Min       |
| Station :        | Station 2     |                      |                        |

### Setting Value

|                                    |        |                   |         |                    |              |           |
|------------------------------------|--------|-------------------|---------|--------------------|--------------|-----------|
| Feeder :                           | Auto ; | 64                | %       | Manual ;           | 20           | RPM       |
| Filling Cam :                      |        | Cam B<br>4.5-10mm |         | Cam Range :        | Min :        | 2.50 mm   |
| Target Quantity :                  |        | 4500000           | Tablets |                    | Max :        | 8.00 mm   |
| Air Pressure Low Limit :           |        | 0.400             | MPa     |                    |              |           |
| Oil Lubrication :                  |        |                   |         |                    |              |           |
| Upper Punch Interval Time(S1) ;    |        | 45                | Min     | Supply Time ;      | 1.0          | Sec       |
| Lower Punch Interval Time(S2) ;    |        | 18                | Min     | Supply Time ;      | 3.0          | Sec       |
| Powder Supply Time :               |        | 5.0               | Sec     |                    |              |           |
| Initial Reject Time :              |        | 2                 | Tablets |                    |              |           |
| Upper Punch Tightness High Limit : |        | 1.00              | kN      |                    |              |           |
| Lower Punch Tightness High Limit : |        | 4.00              | kN      |                    |              |           |
| Ejecting Force High Limit :        |        | 4.00              | kN      |                    |              |           |
|                                    |        |                   |         | Stop Condition ;   |              |           |
| HSP :                              | 30.0 % | 13.42             | kN      | No                 |              |           |
| HEP :                              | 25.0 % | 12.91             | kN      | Yes 10             | Rotations 15 | Tablets   |
| HCP :                              | 2.0 %  | 10.53             | kN      | Yes 15             | Times        |           |
| Ref :                              |        | 10.33             | kN      |                    |              |           |
| LCP :                              | 2.0 %  | 10.12             | kN      | Yes 15             | Times        |           |
| LEP :                              | 25.0 % | 7.74              | kN      | Yes 10             | Rotations 15 | Tablets   |
| LSP :                              | 30.0 % | 7.23              | kN      | No                 |              |           |
| SD limit :                         | 35.0 % |                   |         | Yes                |              |           |
| Pre HSP                            |        | 30.00             | kN      | Yes                |              |           |
| Mean Calculation range :           | 2      | Rotations         |         | Calculation Pass : | 2            | Rotations |
| Empty Punch No. :                  | N      |                   |         |                    |              |           |

### Pressure Data

|                      |            |    |       |            |    |            |    |
|----------------------|------------|----|-------|------------|----|------------|----|
| Mean Pre Pressure :  | 2.69       | kN | Min : | 2.51       | kN | Punch NO.; | 20 |
| SD :                 | 3.50       | %  | Max : | 3.03       | kN | Punch NO.; | 47 |
| Mean Main Pressure : | 10.22      | kN | Min : | 9.25       | kN | Punch NO.; | 45 |
| SD :                 | 4.70       | %  | Max : | 11.45      | kN | Punch NO.; | 7  |
| Filling Depth :      | Increase ; | 18 | Times | Decrease ; | 18 | Times      |    |

## PRODUCTION REPORT

### Operation Value

|                               |         |     |                  |          |              |
|-------------------------------|---------|-----|------------------|----------|--------------|
| Disk Speed :                  | 22      | RPM | Capacity :       | 139920   | Tablets/hour |
| Feeder : Status ;             | Auto    |     | Speed ;          | 14       | RPM          |
| Pre Upper Punch Position ;    | 2.00    | mm  |                  |          |              |
| Pre Lower Punch Position ;    | 5.50    | mm  | Pre Thickness ;  | 3.50     | mm           |
| Main Upper Punch Position ;   | 2.00    | mm  |                  |          |              |
| Main Lower Punch Position ;   | 4.25    | mm  | Main Thickness ; | 2.25     | mm           |
| Filling Depth :               | 6.55    | mm  | Current Cam :    | Cam B    |              |
| Main Air pressure :           | 0.823   | MPa |                  | 4.5-10mm |              |
| Oil Lubrication status :      |         |     |                  |          |              |
| Upper Punch Remain Time (S1): | 32      | Min |                  |          |              |
| Lower Punch Remain Time (S2): | 15      | Min |                  |          |              |
| Lower Head Remain Time (S3):  | 0       | Min |                  |          |              |
| Powder Status :               | Disable |     | Dust Collector : | Off      |              |
| Initial Reject :              | Off     |     | Buzzer :         | Off      |              |

### Tightness

|                  |           |      |    |             |    |
|------------------|-----------|------|----|-------------|----|
| Upper Punch :    | Average ; | 0.00 | kN |             |    |
|                  | Max ;     | 0.04 | kN | Max Punch ; | 17 |
| Lower Punch :    | Average ; | 0.08 | kN |             |    |
|                  | Max ;     | 0.18 | kN | Max Punch ; | 7  |
| Ejection Force : | Average ; | 0.05 | kN |             |    |
|                  | Max ;     | 0.08 | kN | Max Punch ; | 19 |

### Tablet Data (N/A)

|                 |                   |         |       |        |         |
|-----------------|-------------------|---------|-------|--------|---------|
| Total Counter : | 102090            | Tablets |       |        |         |
| A.W.C Counter : | 89634             | Tablets |       |        |         |
| HEP :           | 11 (0.0%)         | Tablets | LEP : | 0 (0%) | Tablets |
| GOOD :          | 89623<br>(100.0%) | Tablets |       |        |         |