

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	am98755	Batch NO. :	EWM2507950
Print Interval :	50000 Tablets	Running Time :	02 Hour 08 Min 53 Sec
Total Counter :	302174	Total Running Time :	1111 Hour 23 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	65	%	Manual ;	15	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		45	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		18	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	13.52	kN	No		
HEP :	25.0 %	13.00	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	10.61	kN	Yes	15	Times
Ref :		10.40	kN			
LCP :	2.0 %	10.19	kN	Yes	15	Times
LEP :	25.0 %	7.80	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	7.28	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	3.25	kN	Min :	2.98	kN	Punch NO.;	13
		3.10	%	Max :	3.48	kN	Punch NO.;	53
Mean Main Pressure :		10.37	kN	Min :	9.38	kN	Punch NO.;	41
	SD :	5.30	%	Max :	11.95	kN	Punch NO.;	22
Filling Depth :	Increase ;	47	Times	Decrease ;	30	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	139920	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	2.00	mm			
Pre Lower Punch Position ;	5.40	mm	Pre Thickness ;	3.40	mm
Main Upper Punch Position ;	2.00	mm			
Main Lower Punch Position ;	4.08	mm	Main Thickness ;	2.08	mm
Filling Depth :	7.20	mm	Current Cam :	Cam B	
Main Air pressure :	0.819	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	36	Min			
Lower Punch Remain Time (S2):	1	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.05	kN	Max Punch ;	43
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.14	kN	Max Punch ;	7
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.08	kN	Max Punch ;	7

Tablet Data (N/A)

Total Counter :	302174	Tablets			
A.W.C Counter :	289709	Tablets			
HEP :	17 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	289692 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	am98755	Batch NO. :	EWM2507950
Print Interval :	50000 Tablets	Running Time :	02 Hour 08 Min 53 Sec
Total Counter :	302174	Total Running Time :	1111 Hour 23 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	64	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		45	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		18	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	13.42	kN	No		
HEP :	25.0 %	12.91	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	10.53	kN	Yes	15	Times
Ref :		10.33	kN			
LCP :	2.0 %	10.12	kN	Yes	15	Times
LEP :	25.0 %	7.74	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	7.23	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.59	kN	Min :	2.39	kN	Punch NO.;	13
SD :	3.20	%	Max :	2.83	kN	Punch NO.;	40
Mean Main Pressure :	10.09	kN	Min :	9.12	kN	Punch NO.;	41
SD :	4.80	%	Max :	10.94	kN	Punch NO.;	14
Filling Depth :	Increase ;	34	Times	Decrease ;	35	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	139920	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	2.00	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	3.50	mm
Main Upper Punch Position ;	2.00	mm			
Main Lower Punch Position ;	4.25	mm	Main Thickness ;	2.25	mm
Filling Depth :	6.49	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.819	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	36	Min			
Lower Punch Remain Time (S2):	1	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.07	kN	Max Punch ;	43
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.14	kN	Max Punch ;	7
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.08	kN	Max Punch ;	7

Tablet Data (N/A)

Total Counter :	302174	Tablets			
A.W.C Counter :	289762	Tablets			
HEP :	17 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	289745 (100.0%)	Tablets			