

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	am98755	Batch NO. :	EWM2507950
Print Interval :	50000 Tablets	Running Time :	02 Hour 30 Min 23 Sec
Total Counter :	352212	Total Running Time :	1111 Hour 44 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	65	%	Manual ;	15	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		45	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		18	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	13.52	kN	No		
HEP :	25.0 %	13.00	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	10.61	kN	Yes 15	Times	
Ref :		10.40	kN			
LCP :	2.0 %	10.19	kN	Yes 15	Times	
LEP :	25.0 %	7.80	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	7.28	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	3.22	kN	Min :	3.02	kN	Punch NO.;	28
		3.00	%	Max :	3.47	kN	Punch NO.;	8
Mean Main Pressure :		10.35	kN	Min :	9.01	kN	Punch NO.;	3
	SD :	4.70	%	Max :	11.47	kN	Punch NO.;	11
Filling Depth :	Increase ;	48	Times	Decrease ;	44	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	139920	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	2.00	mm			
Pre Lower Punch Position ;	5.40	mm	Pre Thickness ;	3.40	mm
Main Upper Punch Position ;	2.00	mm			
Main Lower Punch Position ;	4.08	mm	Main Thickness ;	2.08	mm
Filling Depth :	6.81	mm	Current Cam :	Cam B	
Main Air pressure :	0.766	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	15	Min			
Lower Punch Remain Time (S2):	16	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.07	kN	Max Punch ;	43
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.19	kN	Max Punch ;	7
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.06	kN	Max Punch ;	18

Tablet Data (N/A)

Total Counter :	352212	Tablets			
A.W.C Counter :	339794	Tablets			
HEP :	17 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	339777 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	am98755	Batch NO. :	EWM2507950
Print Interval :	50000 Tablets	Running Time :	02 Hour 30 Min 23 Sec
Total Counter :	352212	Total Running Time :	1111 Hour 44 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	64	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		45	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		18	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	13.42	kN	No		
HEP :	25.0 %	12.91	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	10.53	kN	Yes	15	Times
Ref :		10.33	kN			
LCP :	2.0 %	10.12	kN	Yes	15	Times
LEP :	25.0 %	7.74	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	7.23	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.64	kN	Min :	2.49	kN	Punch NO.;	31
SD :	2.80	%	Max :	2.81	kN	Punch NO.;	53
Mean Main Pressure :	10.36	kN	Min :	9.33	kN	Punch NO.;	41
SD :	4.70	%	Max :	11.54	kN	Punch NO.;	13
Filling Depth :	Increase ;	35	Times	Decrease ;	35	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	139920	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	2.00	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	3.50	mm
Main Upper Punch Position ;	2.00	mm			
Main Lower Punch Position ;	4.25	mm	Main Thickness ;	2.25	mm
Filling Depth :	6.55	mm	Current Cam :	Cam B	
Main Air pressure :	0.766	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	15	Min			
Lower Punch Remain Time (S2):	16	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.07	kN	Max Punch ;	43
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.19	kN	Max Punch ;	7
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.06	kN	Max Punch ;	5

Tablet Data (N/A)

Total Counter :	352212	Tablets			
A.W.C Counter :	339794	Tablets			
HEP :	17 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	339777 (100.0%)	Tablets			