

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	pb97604	Batch NO. :	EWM2507950
Print Interval :	50000 Tablets	Running Time :	03 Hour 56 Min 22 Sec
Total Counter :	552318	Total Running Time :	1113 Hour 10 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	65	%	Manual ;	15	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		45	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		18	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	12.36	kN	No		
HEP :	25.0 %	11.89	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	9.70	kN	Yes	15	Times
Ref :		9.51	kN			
LCP :	2.0 %	9.32	kN	Yes	15	Times
LEP :	25.0 %	7.13	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	6.66	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	3.80	kN	Min :	3.54	kN	Punch NO.;	22
		3.50	%	Max :	4.12	kN	Punch NO.;	8
Mean Main Pressure :	SD :	9.68	kN	Min :	8.87	kN	Punch NO.;	44
		5.40	%	Max :	11.28	kN	Punch NO.;	21
Filling Depth :	Increase ;	72	Times	Decrease ;	87	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	139920	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	2.00	mm			
Pre Lower Punch Position ;	5.30	mm	Pre Thickness ;	3.30	mm
Main Upper Punch Position ;	2.00	mm			
Main Lower Punch Position ;	4.15	mm	Main Thickness ;	2.15	mm
Filling Depth :	6.95	mm	Current Cam :	Cam B	
Main Air pressure :	0.714	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	19	Min			
Lower Punch Remain Time (S2):	3	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.02	kN		
	Max ;	0.10	kN	Max Punch ;	42
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.16	kN	Max Punch ;	7
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.05	kN	Max Punch ;	18

Tablet Data (N/A)

Total Counter :	552318	Tablets			
A.W.C Counter :	539785	Tablets			
HEP :	23 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	539762 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	pb97604	Batch NO. :	EWM2507950
Print Interval :	50000 Tablets	Running Time :	03 Hour 56 Min 22 Sec
Total Counter :	552318	Total Running Time :	1113 Hour 10 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	64	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		45	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		18	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	13.03	kN	No		
HEP :	25.0 %	12.53	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	10.23	kN	Yes	15	Times
Ref :		10.03	kN			
LCP :	2.0 %	9.83	kN	Yes	15	Times
LEP :	25.0 %	7.52	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	7.02	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	3.25	kN	Min :	3.02	kN	Punch NO.;	35
SD :	3.40	%	Max :	3.51	kN	Punch NO.;	8
Mean Main Pressure :	9.89	kN	Min :	8.95	kN	Punch NO.;	44
SD :	5.00	%	Max :	10.96	kN	Punch NO.;	21
Filling Depth :	Increase ;	51	Times	Decrease ;	55	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	139920	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	2.00	mm			
Pre Lower Punch Position ;	5.35	mm	Pre Thickness ;	3.35	mm
Main Upper Punch Position ;	2.00	mm			
Main Lower Punch Position ;	4.32	mm	Main Thickness ;	2.32	mm
Filling Depth :	6.55	mm	Current Cam :	Cam B	
Main Air pressure :	0.714	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	19	Min			
Lower Punch Remain Time (S2):	3	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.02	kN		
	Max ;	0.10	kN	Max Punch ;	43
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.16	kN	Max Punch ;	7
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.05	kN	Max Punch ;	18

Tablet Data (N/A)

Total Counter :	552318	Tablets			
A.W.C Counter :	539785	Tablets			
HEP :	23 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	539762 (100.0%)	Tablets			