

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	sj97904	Batch NO. :	EWM2507950
Print Interval :	50000 Tablets	Running Time :	18 Hour 13 Min 27 Sec
Total Counter :	2547838	Total Running Time :	1127 Hour 26 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	45	%	Manual ;	15	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		100	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	11.43	kN	No		
HEP :	25.0 %	10.99	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	8.97	kN	Yes	15	Times
Ref :		8.79	kN			
LCP :	2.0 %	8.61	kN	Yes	15	Times
LEP :	25.0 %	6.59	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	6.15	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	3.26	kN	Min :	3.09	kN	Punch NO.;	23
		3.60	%	Max :	3.66	kN	Punch NO.;	8
Mean Main Pressure :	SD :	8.60	kN	Min :	7.74	kN	Punch NO.;	3
		5.60	%	Max :	10.15	kN	Punch NO.;	21
Filling Depth :	Increase ;	36	Times	Decrease ;	40	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	139920	Tablets/hour
Feeder : Status ;	Auto		Speed ;	10	RPM
Pre Upper Punch Position ;	2.00	mm			
Pre Lower Punch Position ;	5.44	mm	Pre Thickness ;	3.44	mm
Main Upper Punch Position ;	2.00	mm			
Main Lower Punch Position ;	4.25	mm	Main Thickness ;	2.25	mm
Filling Depth :	6.88	mm	Current Cam :	Cam B	
Main Air pressure :	0.769	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	23	Min			
Lower Punch Remain Time (S2):	24	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.04	kN	Max Punch ;	42
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.15	kN	Max Punch ;	7
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.06	kN	Max Punch ;	53

Tablet Data (N/A)

Total Counter :	2547838	Tablets			
A.W.C Counter :	2532897	Tablets			
HEP :	328 (0.0%)	Tablets	LEP :	31 (0.0%)	Tablets
GOOD :	2532538 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	sj97904	Batch NO. :	EWM2507950
Print Interval :	50000 Tablets	Running Time :	18 Hour 13 Min 27 Sec
Total Counter :	2547838	Total Running Time :	1127 Hour 26 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	38	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		100	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	10.90	kN	No		
HEP :	25.0 %	10.48	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	8.55	kN	Yes 15	Times	
Ref :		8.39	kN			
LCP :	2.0 %	8.22	kN	Yes 15	Times	
LEP :	25.0 %	6.29	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	5.87	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	3.20	kN	Min :	2.90	kN	Punch NO.;	13
SD :	4.00	%	Max :	3.49	kN	Punch NO.;	53
Mean Main Pressure :	8.40	kN	Min :	6.98	kN	Punch NO.;	43
SD :	6.20	%	Max :	9.76	kN	Punch NO.;	13
Filling Depth :	Increase ;	27	Times	Decrease ;	30	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	139920	Tablets/hour
Feeder : Status ;	Auto		Speed ;	8	RPM
Pre Upper Punch Position ;	2.00	mm			
Pre Lower Punch Position ;	5.35	mm	Pre Thickness ;	3.35	mm
Main Upper Punch Position ;	2.00	mm			
Main Lower Punch Position ;	4.46	mm	Main Thickness ;	2.46	mm
Filling Depth :	6.47	mm	Current Cam :	Cam B	
Main Air pressure :	0.769	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	23	Min			
Lower Punch Remain Time (S2):	24	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.05	kN	Max Punch ;	27
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.15	kN	Max Punch ;	7
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.06	kN	Max Punch ;	53

Tablet Data (N/A)

Total Counter :	2547838	Tablets			
A.W.C Counter :	2532897	Tablets			
HEP :	328 (0.0%)	Tablets	LEP :	31 (0.0%)	Tablets
GOOD :	2532538 (100.0%)	Tablets			