

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	pb97604	Batch NO. :	EWM2507950
Print Interval :	50000 Tablets	Running Time :	01 Hour 16 Min 33 Sec
Total Counter :	3498342	Total Running Time :	1134 Hour 30 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	45	%	Manual ;	15	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		100	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	10.39	kN	No		
HEP :	25.0 %	9.99	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	8.15	kN	Yes	15	Times
Ref :		7.99	kN			
LCP :	2.0 %	7.83	kN	Yes	15	Times
LEP :	25.0 %	6.00	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	5.60	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	3.38	kN	Min :	3.20	kN	Punch NO.;	13
SD :	3.00	%	Max :	3.63	kN	Punch NO.;	47
Mean Main Pressure :	8.06	kN	Min :	6.61	kN	Punch NO.;	3
SD :	6.20	%	Max :	9.41	kN	Punch NO.;	21
Filling Depth :	Increase ;	116	Times	Decrease ;	122	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	9	RPM
Pre Upper Punch Position ;	2.00	mm			
Pre Lower Punch Position ;	5.40	mm	Pre Thickness ;	3.40	mm
Main Upper Punch Position ;	2.00	mm			
Main Lower Punch Position ;	4.30	mm	Main Thickness ;	2.30	mm
Filling Depth :	6.82	mm	Current Cam :	Cam B	
Main Air pressure :	0.843	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	46	Min			
Lower Punch Remain Time (S2):	67	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.09	kN		
	Max ;	0.21	kN	Max Punch ;	32
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.13	kN	Max Punch ;	7
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.05	kN	Max Punch ;	52

Tablet Data (N/A)

Total Counter :	3498342	Tablets			
A.W.C Counter :	3483169	Tablets			
HEP :	524 (0.0%)	Tablets	LEP :	68 (0.0%)	Tablets
GOOD :	3482577 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	pb97604	Batch NO. :	EWM2507950
Print Interval :	50000 Tablets	Running Time :	01 Hour 16 Min 33 Sec
Total Counter :	3498342	Total Running Time :	1134 Hour 30 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	38	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		100	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	10.59	kN	No		
HEP :	25.0 %	10.19	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	8.31	kN	Yes 15	Times	
Ref :		8.15	kN			
LCP :	2.0 %	7.99	kN	Yes 15	Times	
LEP :	25.0 %	6.11	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	5.70	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	3.16	kN	Min :	2.98	kN	Punch NO.;	28
SD :	2.70	%	Max :	3.34	kN	Punch NO.;	36
Mean Main Pressure :	8.21	kN	Min :	7.09	kN	Punch NO.;	26
SD :	5.80	%	Max :	9.53	kN	Punch NO.;	21
Filling Depth :	Increase ;	77	Times	Decrease ;	83	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	8	RPM
Pre Upper Punch Position ;	2.00	mm			
Pre Lower Punch Position ;	5.35	mm	Pre Thickness ;	3.35	mm
Main Upper Punch Position ;	2.00	mm			
Main Lower Punch Position ;	4.46	mm	Main Thickness ;	2.46	mm
Filling Depth :	6.41	mm	Current Cam :	Cam B	
Main Air pressure :	0.843	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	46	Min			
Lower Punch Remain Time (S2):	67	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.09	kN		
	Max ;	0.20	kN	Max Punch ;	32
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.13	kN	Max Punch ;	7
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.05	kN	Max Punch ;	52

Tablet Data (N/A)

Total Counter :	3498342	Tablets			
A.W.C Counter :	3483169	Tablets			
HEP :	524 (0.0%)	Tablets	LEP :	68 (0.0%)	Tablets
GOOD :	3482577 (100.0%)	Tablets			