

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	sj97904	Batch NO. :	EWM2508050
Print Interval :	50000 Tablets	Running Time :	14 Hour 51 Min 57 Sec
Total Counter :	2651240	Total Running Time :	1157 Hour 12 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	46	%	Manual ;	15	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		100	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	11.52	kN	No		
HEP :	25.0 %	11.08	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	9.04	kN	Yes 15	Times	
Ref :		8.86	kN			
LCP :	2.0 %	8.69	kN	Yes 15	Times	
LEP :	25.0 %	6.65	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	6.21	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	3.13	kN	Min :	2.94	kN	Punch NO.;	26
SD :	2.80	%	Max :	3.47	kN	Punch NO.;	9
Mean Main Pressure :	8.79	kN	Min :	7.80	kN	Punch NO.;	44
SD :	6.20	%	Max :	11.04	kN	Punch NO.;	21
Filling Depth :	Increase ; 339	Times	Decrease ;	380	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	13	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	6.47	mm	Pre Thickness ;	3.47	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.25	mm	Main Thickness ;	2.25	mm
Filling Depth :	6.99	mm	Current Cam :	Cam B	
Main Air pressure :	0.850	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	1	Min			
Lower Punch Remain Time (S2):	82	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.14	kN		
	Max ;	0.22	kN	Max Punch ;	31
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.10	kN	Max Punch ;	7
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.12	kN	Max Punch ;	14

Tablet Data (N/A)

Total Counter :	2651240	Tablets			
A.W.C Counter :	2645527	Tablets			
HEP :	980 (0.0%)	Tablets	LEP :	619 (0.0%)	Tablets
GOOD :	2643928 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	sj97904	Batch NO. :	EWM2508050
Print Interval :	50000 Tablets	Running Time :	14 Hour 51 Min 57 Sec
Total Counter :	2651240	Total Running Time :	1157 Hour 12 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	49	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		100	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	11.00	kN	No		
HEP :	25.0 %	10.58	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	8.63	kN	Yes 15	Times	
Ref :		8.46	kN			
LCP :	2.0 %	8.29	kN	Yes 15	Times	
LEP :	25.0 %	6.35	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	5.92	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	3.04	kN	Min :	2.82	kN	Punch NO.;	37
SD :	3.10	%	Max :	3.25	kN	Punch NO.;	5
Mean Main Pressure :	8.40	kN	Min :	7.34	kN	Punch NO.;	41
SD :	5.90	%	Max :	9.41	kN	Punch NO.;	49
Filling Depth :	Increase ;	223	Times	Decrease ;	222	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	6.40	mm	Pre Thickness ;	3.40	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.46	mm	Main Thickness ;	2.46	mm
Filling Depth :	6.56	mm	Current Cam :	Cam B	
Main Air pressure :	0.850	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	1	Min			
Lower Punch Remain Time (S2):	82	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.14	kN		
	Max ;	0.22	kN	Max Punch ;	29
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.10	kN	Max Punch ;	7
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.12	kN	Max Punch ;	14

Tablet Data (N/A)

Total Counter :	2651240	Tablets			
A.W.C Counter :	2645580	Tablets			
HEP :	980 (0.0%)	Tablets	LEP :	619 (0.0%)	Tablets
GOOD :	2643981 (99.9%)	Tablets			