

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	sj97904	Batch NO. :	EWM2508350
Print Interval :	50000 Tablets	Running Time :	11 Hour 46 Min 43 Sec
Total Counter :	2100900	Total Running Time :	1179 Hour 20 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	70	%	Manual ;	15	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		100	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	10.57	kN	No		
HEP :	25.0 %	10.16	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	8.29	kN	Yes 10	Times	
Ref :		8.13	kN			
LCP :	2.0 %	7.97	kN	Yes 10	Times	
LEP :	25.0 %	6.10	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	5.69	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.94	kN	Min :	2.75	kN	Punch NO.;	13
SD :	2.60	%	Max :	3.19	kN	Punch NO.;	47
Mean Main Pressure :	8.01	kN	Min :	7.10	kN	Punch NO.;	41
SD :	6.00	%	Max :	9.05	kN	Punch NO.;	49
Filling Depth :	Increase ;	1122	Times	Decrease ;	1166	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	20	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	6.47	mm	Pre Thickness ;	3.47	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.26	mm	Main Thickness ;	2.26	mm
Filling Depth :	7.34	mm	Current Cam :	Cam B	
Main Air pressure :	0.840	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	55	Min			
Lower Punch Remain Time (S2):	16	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.12	kN		
	Max ;	0.22	kN	Max Punch ;	37
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.11	kN	Max Punch ;	7
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.18	kN	Max Punch ;	14

Tablet Data (N/A)

Total Counter :	2100900	Tablets			
A.W.C Counter :	2093916	Tablets			
HEP :	1308 (0.1%)	Tablets	LEP :	460 (0.0%)	Tablets
GOOD :	2092148 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	sj97904	Batch NO. :	EWM2508350
Print Interval :	50000 Tablets	Running Time :	11 Hour 46 Min 43 Sec
Total Counter :	2100900	Total Running Time :	1179 Hour 20 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	68	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		100	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	10.59	kN	No		
HEP :	25.0 %	10.19	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	8.31	kN	Yes 10	Times	
Ref :		8.15	kN			
LCP :	2.0 %	7.99	kN	Yes 10	Times	
LEP :	25.0 %	6.11	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	5.70	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.91	kN	Min :	2.63	kN	Punch NO.;	13
SD :	2.80	%	Max :	3.07	kN	Punch NO.;	8
Mean Main Pressure :	8.14	kN	Min :	7.24	kN	Punch NO.;	41
SD :	5.40	%	Max :	8.99	kN	Punch NO.;	13
Filling Depth :	Increase ;	680	Times	Decrease ;	680	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	19	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.39	mm	Pre Thickness ;	3.40	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.46	mm	Main Thickness ;	2.47	mm
Filling Depth :	6.97	mm	Current Cam :	Cam B	
Main Air pressure :	0.840	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	55	Min			
Lower Punch Remain Time (S2):	16	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.12	kN		
	Max ;	0.22	kN	Max Punch ;	37
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.11	kN	Max Punch ;	7
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.16	kN	Max Punch ;	14

Tablet Data (N/A)

Total Counter :	2100900	Tablets			
A.W.C Counter :	2093916	Tablets			
HEP :	1308 (0.1%)	Tablets	LEP :	460 (0.0%)	Tablets
GOOD :	2092148 (99.9%)	Tablets			