

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	pb97604	Batch NO. :	EWM2508350
Print Interval :	50000 Tablets	Running Time :	22 Hour 07 Min 05 Sec
Total Counter :	3945694	Total Running Time :	1189 Hour 40 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	91	%	Manual ;	15	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		100	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	10.34	kN	No		
HEP :	25.0 %	9.94	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	8.11	kN	Yes 10	Times	
Ref :		7.96	kN			
LCP :	2.0 %	7.80	kN	Yes 10	Times	
LEP :	25.0 %	5.97	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	5.57	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.95	kN	Min :	2.81	kN	Punch NO.;	6
SD :	2.20	%	Max :	3.08	kN	Punch NO.;	25
Mean Main Pressure :	7.79	kN	Min :	7.11	kN	Punch NO.;	3
SD :	5.00	%	Max :	8.69	kN	Punch NO.;	21
Filling Depth :	Increase ; 59	Times	Decrease ; 70	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	25	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	6.46	mm	Pre Thickness ;	3.46	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.26	mm	Main Thickness ;	2.26	mm
Filling Depth :	7.27	mm	Current Cam :	Cam B	
Main Air pressure :	0.840	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	24	Min			
Lower Punch Remain Time (S2):	45	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.11	kN		
	Max ;	0.19	kN	Max Punch ;	37
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.11	kN	Max Punch ;	7
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.08	kN	Max Punch ;	52

Tablet Data (N/A)

Total Counter :	3945694	Tablets			
A.W.C Counter :	3937850	Tablets			
HEP :	2049 (0.1%)	Tablets	LEP :	722 (0.0%)	Tablets
GOOD :	3935079 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	pb97604	Batch NO. :	EWM2508350
Print Interval :	50000 Tablets	Running Time :	22 Hour 07 Min 05 Sec
Total Counter :	3945694	Total Running Time :	1189 Hour 40 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	91	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		100	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	10.33	kN	No		
HEP :	25.0 %	9.93	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	8.10	kN	Yes	10 Times	
Ref :		7.95	kN			
LCP :	2.0 %	7.79	kN	Yes	10 Times	
LEP :	25.0 %	5.96	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	5.56	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.90	kN	Min :	2.67	kN	Punch NO.;	13
SD :	3.00	%	Max :	3.09	kN	Punch NO.;	8
Mean Main Pressure :	7.86	kN	Min :	6.84	kN	Punch NO.;	43
SD :	6.50	%	Max :	9.07	kN	Punch NO.;	21
Filling Depth :	Increase ;	43	Times	Decrease ;	44	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	25	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.39	mm	Pre Thickness ;	3.40	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.46	mm	Main Thickness ;	2.47	mm
Filling Depth :	6.91	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.840	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	24	Min			
Lower Punch Remain Time (S2):	45	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.10	kN		
	Max ;	0.18	kN	Max Punch ;	31
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.11	kN	Max Punch ;	7
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.08	kN	Max Punch ;	52

Tablet Data (N/A)

Total Counter :	3945694	Tablets			
A.W.C Counter :	3937850	Tablets			
HEP :	2049 (0.1%)	Tablets	LEP :	722 (0.0%)	Tablets
GOOD :	3935079 (99.9%)	Tablets			