

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	sj97904	Batch NO. :	EWM2508950
Print Interval :	50000 Tablets	Running Time :	00 Hour 20 Min 14 Sec
Total Counter :	4156858	Total Running Time :	1217 Hour 2 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	96	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		120	Min	Supply Time ;	1.5	Sec
Lower Punch Interval Time(S2) ;		120	Min	Supply Time ;	1.8	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	28.20	kN	No		
HEP :	25.0 %	27.12	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	22.13	kN	Yes	10 Times	
Ref :		21.69	kN			
LCP :	2.0 %	21.26	kN	Yes	10 Times	
LEP :	25.0 %	16.27	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	15.18	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.91	kN	Min :	2.73	kN	Punch NO.;	17
SD :	2.50	%	Max :	3.05	kN	Punch NO.;	4
Mean Main Pressure :	21.60	kN	Min :	19.83	kN	Punch NO.;	30
SD :	3.70	%	Max :	23.57	kN	Punch NO.;	20
Filling Depth :	Increase ;	189	Times	Decrease ;	150	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	27	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	6.46	mm	Pre Thickness ;	3.46	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.29	mm	Main Thickness ;	2.30	mm
Filling Depth :	7.55	mm	Current Cam :	Cam C	
Main Air pressure :	0.834	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	102	Min			
Lower Punch Remain Time (S2):	103	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	On	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.17	kN		
	Max ;	0.25	kN	Max Punch ;	35
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.15	kN	Max Punch ;	27
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	4156858	Tablets			
A.W.C Counter :	4137056	Tablets			
HEP :	340 (0.0%)	Tablets	LEP :	715 (0.0%)	Tablets
GOOD :	4136001 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	sj97904	Batch NO. :	EWM2508950
Print Interval :	50000 Tablets	Running Time :	00 Hour 20 Min 14 Sec
Total Counter :	4156858	Total Running Time :	1217 Hour 2 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	85	%	Manual ;	20	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		120	Min	Supply Time ;	1.5	Sec
Lower Punch Interval Time(S2) ;		120	Min	Supply Time ;	1.8	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	28.11	kN	No		
HEP :	25.0 %	27.03	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	22.06	kN	Yes	10 Times	
Ref :		21.62	kN			
LCP :	2.0 %	21.19	kN	Yes	10 Times	
LEP :	25.0 %	16.22	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	15.14	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.73	kN	Min :	2.56	kN	Punch NO.;	16
SD :	3.20	%	Max :	2.89	kN	Punch NO.;	25
Mean Main Pressure :	21.44	kN	Min :	19.31	kN	Punch NO.;	30
SD :	4.30	%	Max :	23.35	kN	Punch NO.;	38
Filling Depth :	Increase ;	78	Times	Decrease ;	86	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	24	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.40	mm	Pre Thickness ;	3.41	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.44	mm	Main Thickness ;	2.45	mm
Filling Depth :	7.29	mm	Current Cam :	Cam C	
Main Air pressure :	0.834	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	102	Min			
Lower Punch Remain Time (S2):	103	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	On	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.17	kN		
	Max ;	0.25	kN	Max Punch ;	35
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.15	kN	Max Punch ;	27
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	4156858	Tablets			
A.W.C Counter :	4137056	Tablets			
HEP :	340 (0.0%)	Tablets	LEP :	715 (0.0%)	Tablets
GOOD :	4136001 (100.0%)	Tablets			