

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	sj97904	Batch NO. :	EWM2509450
Print Interval :	50000 Tablets	Running Time :	02 Hour 48 Min 32 Sec
Total Counter :	500284	Total Running Time :	1221 Hour 43 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	72	%	Manual ;	15	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		120	Min	Supply Time ;	1.5	Sec
Lower Punch Interval Time(S2) ;		120	Min	Supply Time ;	1.8	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	13.94	kN	No		
HEP :	25.0 %	13.40	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	10.94	kN	Yes 10	Times	
Ref :		10.72	kN			
LCP :	2.0 %	10.51	kN	Yes 10	Times	
LEP :	25.0 %	8.04	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	7.51	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	3.07	kN	Min :	2.86	kN	Punch NO.;	17
		3.30	%	Max :	3.30	kN	Punch NO.;	48
Mean Main Pressure :	SD :	11.00	kN	Min :	9.47	kN	Punch NO.;	29
		6.00	%	Max :	12.17	kN	Punch NO.;	26
Filling Depth :	Increase ;	409	Times	Decrease ;	369	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	20	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	6.46	mm	Pre Thickness ;	3.46	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.34	mm	Main Thickness ;	2.35	mm
Filling Depth :	7.30	mm	Current Cam :	Cam B	
Main Air pressure :	0.807	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	2	Min			
Lower Punch Remain Time (S2):	3	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.19	kN		
	Max ;	0.27	kN	Max Punch ;	44
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.19	kN	Max Punch ;	27
Ejection Force :	Average ;	0.27	kN		
	Max ;	0.29	kN	Max Punch ;	10

Tablet Data (N/A)

Total Counter :	500284	Tablets			
A.W.C Counter :	496538	Tablets			
HEP :	227 (0.0%)	Tablets	LEP :	298 (0.1%)	Tablets
GOOD :	496013 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	sj97904	Batch NO. :	EWM2509450
Print Interval :	50000 Tablets	Running Time :	02 Hour 48 Min 32 Sec
Total Counter :	500284	Total Running Time :	1221 Hour 43 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	73	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		120	Min	Supply Time ;	1.5	Sec
Lower Punch Interval Time(S2) ;		120	Min	Supply Time ;	1.8	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	13.18	kN	No		
HEP :	25.0 %	12.67	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	10.34	kN	Yes 10	Times	
Ref :		10.14	kN			
LCP :	2.0 %	9.94	kN	Yes 10	Times	
LEP :	25.0 %	7.60	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	7.10	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.85	kN	Min :	2.60	kN	Punch NO.;	27
SD :	3.90	%	Max :	3.12	kN	Punch NO.;	40
Mean Main Pressure :	10.24	kN	Min :	9.08	kN	Punch NO.;	30
SD :	6.00	%	Max :	11.66	kN	Punch NO.;	38
Filling Depth :	Increase ;	266	Times	Decrease ;	271	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	20	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.40	mm	Pre Thickness ;	3.41	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.48	mm	Main Thickness ;	2.49	mm
Filling Depth :	6.90	mm	Current Cam :	Cam B	
Main Air pressure :	0.807	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	2	Min			
Lower Punch Remain Time (S2):	3	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.19	kN		
	Max ;	0.28	kN	Max Punch ;	44
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.19	kN	Max Punch ;	27
Ejection Force :	Average ;	0.27	kN		
	Max ;	0.29	kN	Max Punch ;	10

Tablet Data (N/A)

Total Counter :	500284	Tablets			
A.W.C Counter :	496538	Tablets			
HEP :	227 (0.0%)	Tablets	LEP :	298 (0.1%)	Tablets
GOOD :	496013 (99.9%)	Tablets			