

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	sj97904	Batch NO. :	EWM2509450
Print Interval :	50000 Tablets	Running Time :	09 Hour 54 Min 50 Sec
Total Counter :	1767220	Total Running Time :	1228 Hour 50 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	86	%	Manual ;	15	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	13.68	kN	No		
HEP :	25.0 %	13.15	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	10.73	kN	Yes	10 Times	
Ref :		10.52	kN			
LCP :	2.0 %	10.31	kN	Yes	10 Times	
LEP :	25.0 %	7.89	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	7.36	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	3.04	kN	Min :	2.80	kN	Punch NO.;	27
		3.50	%	Max :	3.30	kN	Punch NO.;	9
Mean Main Pressure :		10.75	kN	Min :	9.51	kN	Punch NO.;	29
	SD :	5.40	%	Max :	12.56	kN	Punch NO.;	26
Filling Depth :	Increase ;	533	Times	Decrease ;	533	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	24	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	6.46	mm	Pre Thickness ;	3.46	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.34	mm	Main Thickness ;	2.35	mm
Filling Depth :	7.09	mm	Current Cam :	Cam B	
Main Air pressure :	0.781	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	8	Min			
Lower Punch Remain Time (S2):	8	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.20	kN		
	Max ;	0.28	kN	Max Punch ;	42
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.10	kN	Max Punch ;	20
Ejection Force :	Average ;	0.19	kN		
	Max ;	0.33	kN	Max Punch ;	10

Tablet Data (N/A)

Total Counter :	1767220	Tablets			
A.W.C Counter :	1761091	Tablets			
HEP :	601 (0.0%)	Tablets	LEP :	443 (0.0%)	Tablets
GOOD :	1760047 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	sj97904	Batch NO. :	EWM2509450
Print Interval :	50000 Tablets	Running Time :	09 Hour 54 Min 50 Sec
Total Counter :	1767220	Total Running Time :	1228 Hour 50 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	64	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	12.99	kN	No		
HEP :	25.0 %	12.49	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	10.19	kN	Yes	10 Times	
Ref :		9.99	kN			
LCP :	2.0 %	9.79	kN	Yes	10 Times	
LEP :	25.0 %	7.49	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	7.00	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.72	kN	Min :	2.53	kN	Punch NO.;	16
SD :	3.70	%	Max :	3.06	kN	Punch NO.;	51
Mean Main Pressure :	9.87	kN	Min :	8.50	kN	Punch NO.;	30
SD :	6.50	%	Max :	11.55	kN	Punch NO.;	11
Filling Depth :	Increase ;	244	Times	Decrease ;	237	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	18	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.40	mm	Pre Thickness ;	3.41	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.48	mm	Main Thickness ;	2.49	mm
Filling Depth :	6.89	mm	Current Cam :	Cam B	
Main Air pressure :	0.781	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	8	Min			
Lower Punch Remain Time (S2):	8	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.21	kN		
	Max ;	0.30	kN	Max Punch ;	31
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.10	kN	Max Punch ;	20
Ejection Force :	Average ;	0.19	kN		
	Max ;	0.33	kN	Max Punch ;	10

Tablet Data (N/A)

Total Counter :	1767220	Tablets			
A.W.C Counter :	1761144	Tablets			
HEP :	601 (0.0%)	Tablets	LEP :	443 (0.0%)	Tablets
GOOD :	1760100 (99.9%)	Tablets			