

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	sj97904	Batch NO. :	EWM2509850
Print Interval :	50000 Tablets	Running Time :	03 Hour 38 Min 42 Sec
Total Counter :	650316	Total Running Time :	1247 Hour 44 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	84	%	Manual ;	15	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	13.79	kN	No		
HEP :	25.0 %	13.26	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	10.82	kN	Yes 15	Times	
Ref :		10.61	kN			
LCP :	2.0 %	10.39	kN	Yes 15	Times	
LEP :	25.0 %	7.96	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	7.42	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	3.14	kN	Min :	2.85	kN	Punch NO.;	22
SD :	3.00	%	Max :	3.33	kN	Punch NO.;	25
Mean Main Pressure :	10.58	kN	Min :	9.56	kN	Punch NO.;	15
SD :	5.20	%	Max :	12.09	kN	Punch NO.;	26
Filling Depth :	Increase ; 360	Times	Decrease ;	398	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	24	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	6.46	mm	Pre Thickness ;	3.46	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.33	mm	Main Thickness ;	2.34	mm
Filling Depth :	7.05	mm	Current Cam :	Cam B	
Main Air pressure :	0.807	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	14	Min			
Lower Punch Remain Time (S2):	14	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	On	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.10	kN		
	Max ;	0.17	kN	Max Punch ;	34
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.09	kN	Max Punch ;	29
Ejection Force :	Average ;	0.02	kN		
	Max ;	0.19	kN	Max Punch ;	24

Tablet Data (N/A)

Total Counter :	650316	Tablets			
A.W.C Counter :	645878	Tablets			
HEP :	107 (0.0%)	Tablets	LEP :	1 (0.0%)	Tablets
GOOD :	645770 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	sj97904	Batch NO. :	EWM2509850
Print Interval :	50000 Tablets	Running Time :	03 Hour 38 Min 42 Sec
Total Counter :	650316	Total Running Time :	1247 Hour 44 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	64	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	13.08	kN	No		
HEP :	25.0 %	12.58	kN	Yes	10 Rotations	15 Tablets
HCP :	2.0 %	10.26	kN	Yes	15 Times	
Ref :		10.06	kN			
LCP :	2.0 %	9.86	kN	Yes	15 Times	
LEP :	25.0 %	7.55	kN	Yes	10 Rotations	15 Tablets
LSP :	30.0 %	7.04	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.93	kN	Min :	2.73	kN	Punch NO.;	17
SD :	3.60	%	Max :	3.19	kN	Punch NO.;	25
Mean Main Pressure :	10.07	kN	Min :	8.52	kN	Punch NO.;	30
SD :	7.00	%	Max :	11.65	kN	Punch NO.;	38
Filling Depth :	Increase ;	292	Times	Decrease ;	289	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	18	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.40	mm	Pre Thickness ;	3.41	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.49	mm	Main Thickness ;	2.50	mm
Filling Depth :	6.90	mm	Current Cam :	Cam B	
Main Air pressure :	0.807	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	14	Min			
Lower Punch Remain Time (S2):	14	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	On	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.10	kN		
	Max ;	0.18	kN	Max Punch ;	34
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.09	kN	Max Punch ;	29
Ejection Force :	Average ;	0.02	kN		
	Max ;	0.19	kN	Max Punch ;	24

Tablet Data (N/A)

Total Counter :	650316	Tablets			
A.W.C Counter :	645878	Tablets			
HEP :	107 (0.0%)	Tablets	LEP :	1 (0.0%)	Tablets
GOOD :	645770 (100.0%)	Tablets			