

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	sj97904	Batch NO. :	EWM2509850
Print Interval :	50000 Tablets	Running Time :	05 Hour 53 Min 14 Sec
Total Counter :	1050500	Total Running Time :	1249 Hour 58 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	84	%	Manual ;	15	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	13.92	kN	No		
HEP :	25.0 %	13.38	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	10.92	kN	Yes	15	Times
Ref :		10.71	kN			
LCP :	2.0 %	10.49	kN	Yes	15	Times
LEP :	25.0 %	8.03	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	7.49	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	3.19	kN	Min :	2.98	kN	Punch NO.;	22
SD :	2.90	%	Max :	3.41	kN	Punch NO.;	43
Mean Main Pressure :	10.80	kN	Min :	9.24	kN	Punch NO.;	15
SD :	5.70	%	Max :	11.98	kN	Punch NO.;	24
Filling Depth :	Increase ;	429	Times	Decrease ;	475	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	24	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	6.46	mm	Pre Thickness ;	3.46	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.33	mm	Main Thickness ;	2.34	mm
Filling Depth :	7.06	mm	Current Cam :	Cam B	
Main Air pressure :	0.813	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	20	Min			
Lower Punch Remain Time (S2):	20	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	On	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.10	kN		
	Max ;	0.18	kN	Max Punch ;	28
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.10	kN	Max Punch ;	27
Ejection Force :	Average ;	0.02	kN		
	Max ;	0.20	kN	Max Punch ;	24

Tablet Data (N/A)

Total Counter :	1050500	Tablets			
A.W.C Counter :	1045962	Tablets			
HEP :	169 (0.0%)	Tablets	LEP :	2 (0.0%)	Tablets
GOOD :	1045791 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	sj97904	Batch NO. :	EWM2509850
Print Interval :	50000 Tablets	Running Time :	05 Hour 53 Min 14 Sec
Total Counter :	1050500	Total Running Time :	1249 Hour 58 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	64	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	13.10	kN	No		
HEP :	25.0 %	12.60	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	10.28	kN	Yes	15	Times
Ref :		10.08	kN			
LCP :	2.0 %	9.88	kN	Yes	15	Times
LEP :	25.0 %	7.56	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	7.06	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.99	kN	Min :	2.81	kN	Punch NO.;	52
SD :	3.30	%	Max :	3.27	kN	Punch NO.;	42
Mean Main Pressure :	10.34	kN	Min :	8.45	kN	Punch NO.;	29
SD :	6.60	%	Max :	11.94	kN	Punch NO.;	24
Filling Depth :	Increase ;	378	Times	Decrease ;	376	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	18	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.40	mm	Pre Thickness ;	3.41	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.49	mm	Main Thickness ;	2.50	mm
Filling Depth :	6.87	mm	Current Cam :	Cam B	
Main Air pressure :	0.813	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	20	Min			
Lower Punch Remain Time (S2):	20	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	On	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.10	kN		
	Max ;	0.18	kN	Max Punch ;	28
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.10	kN	Max Punch ;	27
Ejection Force :	Average ;	0.02	kN		
	Max ;	0.16	kN	Max Punch ;	24

Tablet Data (N/A)

Total Counter :	1050500	Tablets			
A.W.C Counter :	1045962	Tablets			
HEP :	169 (0.0%)	Tablets	LEP :	2 (0.0%)	Tablets
GOOD :	1045791 (100.0%)	Tablets			