

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	yu98249	Batch NO. :	EWM2510050
Print Interval :	50000 Tablets	Running Time :	01 Hour 24 Min 20 Sec
Total Counter :	250170	Total Running Time :	1270 Hour 39 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	50	%	Manual ;	15	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	26.50	kN	No		
HEP :	25.0 %	25.48	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	20.80	kN	Yes 15	Times	
Ref :		20.39	kN			
LCP :	2.0 %	19.98	kN	Yes 15	Times	
LEP :	25.0 %	15.29	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	14.27	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.85	kN	Min :	2.71	kN	Punch NO.;	19
SD :	3.20	%	Max :	3.18	kN	Punch NO.;	29
Mean Main Pressure :	20.05	kN	Min :	18.47	kN	Punch NO.;	30
SD :	3.20	%	Max :	21.52	kN	Punch NO.;	51
Filling Depth :	Increase ;	311	Times	Decrease ;	299	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	6.46	mm	Pre Thickness ;	3.46	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.33	mm	Main Thickness ;	2.34	mm
Filling Depth :	8.09	mm	Current Cam :	Cam C	
Main Air pressure :	0.808	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	3	Min			
Lower Punch Remain Time (S2):	3	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.08	kN		
	Max ;	0.16	kN	Max Punch ;	28
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.09	kN	Max Punch ;	27
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.18	kN	Max Punch ;	24

Tablet Data (N/A)

Total Counter :	250170	Tablets			
A.W.C Counter :	245211	Tablets			
HEP :	22 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	245189 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	yu98249	Batch NO. :	EWM2510050
Print Interval :	50000 Tablets	Running Time :	01 Hour 24 Min 20 Sec
Total Counter :	250170	Total Running Time :	1270 Hour 39 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	50	%	Manual ;	20	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	25.81	kN	No		
HEP :	25.0 %	24.81	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	20.25	kN	Yes	15	Times
Ref :		19.85	kN			
LCP :	2.0 %	19.45	kN	Yes	15	Times
LEP :	25.0 %	14.89	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	13.90	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.65	kN	Min :	2.44	kN	Punch NO.;	27
SD :	3.30	%	Max :	2.82	kN	Punch NO.;	40
Mean Main Pressure :	19.59	kN	Min :	18.15	kN	Punch NO.;	29
SD :	3.90	%	Max :	21.38	kN	Punch NO.;	38
Filling Depth :	Increase ;	230	Times	Decrease ;	226	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.40	mm	Pre Thickness ;	3.41	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.49	mm	Main Thickness ;	2.50	mm
Filling Depth :	7.49	mm	Current Cam :	Cam C	
Main Air pressure :	0.808	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	3	Min			
Lower Punch Remain Time (S2):	3	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.08	kN		
	Max ;	0.16	kN	Max Punch ;	28
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.09	kN	Max Punch ;	27
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.20	kN	Max Punch ;	21

Tablet Data (N/A)

Total Counter :	250170	Tablets			
A.W.C Counter :	245211	Tablets			
HEP :	22 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	245189 (100.0%)	Tablets			