

## PRODUCTION REPORT

### Product Information

|                  |               |                      |                        |
|------------------|---------------|----------------------|------------------------|
| Machine Name :   | VANTIX P720D  | Product Name :       | MET 500<br>MG,STEW1A00 |
| User ID :        | yu98249       | Batch NO. :          | EWM2510050             |
| Print Interval : | 50000 Tablets | Running Time :       | 07 Hour 34 Min 22 Sec  |
| Total Counter :  | 1350728       | Total Running Time : | 1276 Hour 50 Min       |
| Station :        | Station 1     |                      |                        |

### Setting Value

|                                    |             |                   |         |                    |              |           |
|------------------------------------|-------------|-------------------|---------|--------------------|--------------|-----------|
| Feeder :                           | Auto ;      | 50                | %       | Manual ;           | 15           | RPM       |
| Filling Cam :                      |             | Cam C<br>8.5-14mm |         | Cam Range :        | Min :        | 6.50 mm   |
| Target Quantity :                  |             | 4500000           | Tablets |                    | Max :        | 12.00 mm  |
| Air Pressure Low Limit :           |             | 0.400             | MPa     |                    |              |           |
| Oil Lubrication :                  |             |                   |         |                    |              |           |
| Upper Punch Interval Time(S1) ;    |             | 20                | Min     | Supply Time ;      | 1.0          | Sec       |
| Lower Punch Interval Time(S2) ;    |             | 20                | Min     | Supply Time ;      | 1.0          | Sec       |
| Powder Supply Time :               |             | 5.0               | Sec     |                    |              |           |
| Initial Reject Time :              |             | 1                 | Tablets |                    |              |           |
| Upper Punch Tightness High Limit : |             | 1.00              | kN      |                    |              |           |
| Lower Punch Tightness High Limit : |             | 4.00              | kN      |                    |              |           |
| Ejecting Force High Limit :        |             | 4.00              | kN      |                    |              |           |
|                                    |             |                   |         | Stop Condition ;   |              |           |
| HSP :                              | 30.0 %      | 26.50             | kN      | No                 |              |           |
| HEP :                              | 25.0 %      | 25.48             | kN      | Yes 10             | Rotations 15 | Tablets   |
| HCP :                              | 2.0 %       | 20.80             | kN      | Yes 15             | Times        |           |
| Ref :                              |             | 20.39             | kN      |                    |              |           |
| LCP :                              | 2.0 %       | 19.98             | kN      | Yes 15             | Times        |           |
| LEP :                              | 25.0 %      | 15.29             | kN      | Yes 10             | Rotations 15 | Tablets   |
| LSP :                              | 30.0 %      | 14.27             | kN      | No                 |              |           |
| SD limit :                         | 35.0 %      |                   |         | Yes                |              |           |
| Pre HSP                            |             | 30.00             | kN      | Yes                |              |           |
| Mean Calculation range :           | 2 Rotations |                   |         | Calculation Pass : | 2            | Rotations |
| Empty Punch No. :                  | None        |                   |         |                    |              |           |

### Pressure Data

|                      |            |     |       |            |     |            |    |
|----------------------|------------|-----|-------|------------|-----|------------|----|
| Mean Pre Pressure :  | 2.79       | kN  | Min : | 2.61       | kN  | Punch NO.; | 14 |
| SD :                 | 3.60       | %   | Max : | 3.03       | kN  | Punch NO.; | 38 |
| Mean Main Pressure : | 20.19      | kN  | Min : | 19.04      | kN  | Punch NO.; | 18 |
| SD :                 | 3.10       | %   | Max : | 21.55      | kN  | Punch NO.; | 26 |
| Filling Depth :      | Increase ; | 527 | Times | Decrease ; | 492 | Times      |    |

## PRODUCTION REPORT

### Operation Value

|                               |        |     |                  |          |              |
|-------------------------------|--------|-----|------------------|----------|--------------|
| Disk Speed :                  | 28     | RPM | Capacity :       | 178080   | Tablets/hour |
| Feeder : Status ;             | Auto   |     | Speed ;          | 14       | RPM          |
| Pre Upper Punch Position ;    | 3.00   | mm  |                  |          |              |
| Pre Lower Punch Position ;    | 6.46   | mm  | Pre Thickness ;  | 3.46     | mm           |
| Main Upper Punch Position ;   | 2.99   | mm  |                  |          |              |
| Main Lower Punch Position ;   | 5.33   | mm  | Main Thickness ; | 2.34     | mm           |
| Filling Depth :               | 7.75   | mm  | Current Cam :    | Cam C    |              |
| Main Air pressure :           | 0.814  | MPa |                  | 8.5-14mm |              |
| Oil Lubrication status :      |        |     |                  |          |              |
| Upper Punch Remain Time (S1): | 3      | Min |                  |          |              |
| Lower Punch Remain Time (S2): | 3      | Min |                  |          |              |
| Lower Head Remain Time (S3):  | 0      | Min |                  |          |              |
| Powder Status :               | Enable |     | Dust Collector : | Off      |              |
| Initial Reject :              | Off    |     | Buzzer :         | Off      |              |

### Tightness

|                  |           |      |    |             |    |
|------------------|-----------|------|----|-------------|----|
| Upper Punch :    | Average ; | 0.11 | kN |             |    |
|                  | Max ;     | 0.23 | kN | Max Punch ; | 28 |
| Lower Punch :    | Average ; | 0.07 | kN |             |    |
|                  | Max ;     | 0.09 | kN | Max Punch ; | 29 |
| Ejection Force : | Average ; | 0.03 | kN |             |    |
|                  | Max ;     | 0.19 | kN | Max Punch ; | 12 |

### Tablet Data (N/A)

|                 |                  |         |       |        |         |
|-----------------|------------------|---------|-------|--------|---------|
| Total Counter : | 1350728          | Tablets |       |        |         |
| A.W.C Counter : | 1345352          | Tablets |       |        |         |
| HEP :           | 24 (0.0%)        | Tablets | LEP : | 0 (0%) | Tablets |
| GOOD :          | 1345328 (100.0%) | Tablets |       |        |         |

## PRODUCTION REPORT

### Product Information

|                  |               |                      |                        |
|------------------|---------------|----------------------|------------------------|
| Machine Name :   | VANTIX P720D  | Product Name :       | MET 500<br>MG,STEW1A00 |
| User ID :        | yu98249       | Batch NO. :          | EWM2510050             |
| Print Interval : | 50000 Tablets | Running Time :       | 07 Hour 34 Min 22 Sec  |
| Total Counter :  | 1350728       | Total Running Time : | 1276 Hour 50 Min       |
| Station :        | Station 2     |                      |                        |

### Setting Value

|                                    |        |                   |         |                    |       |                      |
|------------------------------------|--------|-------------------|---------|--------------------|-------|----------------------|
| Feeder :                           | Auto ; | 50                | %       | Manual ;           | 20    | RPM                  |
| Filling Cam :                      |        | Cam C<br>8.5-14mm |         | Cam Range :        | Min : | 6.50 mm              |
| Target Quantity :                  |        | 4500000           | Tablets |                    | Max : | 12.00 mm             |
| Air Pressure Low Limit :           |        | 0.400             | MPa     |                    |       |                      |
| Oil Lubrication :                  |        |                   |         |                    |       |                      |
| Upper Punch Interval Time(S1) ;    |        | 20                | Min     | Supply Time ;      | 1.0   | Sec                  |
| Lower Punch Interval Time(S2) ;    |        | 20                | Min     | Supply Time ;      | 1.0   | Sec                  |
| Powder Supply Time :               |        | 5.0               | Sec     |                    |       |                      |
| Initial Reject Time :              |        | 1                 | Tablets |                    |       |                      |
| Upper Punch Tightness High Limit : |        | 1.00              | kN      |                    |       |                      |
| Lower Punch Tightness High Limit : |        | 4.00              | kN      |                    |       |                      |
| Ejecting Force High Limit :        |        | 4.00              | kN      |                    |       |                      |
|                                    |        |                   |         | Stop Condition ;   |       |                      |
| HSP :                              | 30.0 % | 25.81             | kN      | No                 |       |                      |
| HEP :                              | 25.0 % | 24.81             | kN      | Yes                | 10    | Rotations 15 Tablets |
| HCP :                              | 2.0 %  | 20.25             | kN      | Yes                | 15    | Times                |
| Ref :                              |        | 19.85             | kN      |                    |       |                      |
| LCP :                              | 2.0 %  | 19.45             | kN      | Yes                | 15    | Times                |
| LEP :                              | 25.0 % | 14.89             | kN      | Yes                | 10    | Rotations 15 Tablets |
| LSP :                              | 30.0 % | 13.90             | kN      | No                 |       |                      |
| SD limit :                         | 35.0 % |                   |         | Yes                |       |                      |
| Pre HSP                            |        | 30.00             | kN      | Yes                |       |                      |
| Mean Calculation range :           | 2      | Rotations         |         | Calculation Pass : | 2     | Rotations            |
| Empty Punch No. :                  | N      |                   |         |                    |       |                      |

### Pressure Data

|                      |            |     |       |            |     |            |    |
|----------------------|------------|-----|-------|------------|-----|------------|----|
| Mean Pre Pressure :  | 2.60       | kN  | Min : | 2.42       | kN  | Punch NO.; | 16 |
| SD :                 | 3.50       | %   | Max : | 2.86       | kN  | Punch NO.; | 10 |
| Mean Main Pressure : | 19.73      | kN  | Min : | 17.92      | kN  | Punch NO.; | 29 |
| SD :                 | 4.10       | %   | Max : | 21.23      | kN  | Punch NO.; | 53 |
| Filling Depth :      | Increase ; | 289 | Times | Decrease ; | 284 | Times      |    |

## PRODUCTION REPORT

### Operation Value

|                               |        |     |                  |          |              |
|-------------------------------|--------|-----|------------------|----------|--------------|
| Disk Speed :                  | 28     | RPM | Capacity :       | 178080   | Tablets/hour |
| Feeder : Status ;             | Auto   |     | Speed ;          | 14       | RPM          |
| Pre Upper Punch Position ;    | 2.99   | mm  |                  |          |              |
| Pre Lower Punch Position ;    | 6.40   | mm  | Pre Thickness ;  | 3.41     | mm           |
| Main Upper Punch Position ;   | 2.99   | mm  |                  |          |              |
| Main Lower Punch Position ;   | 5.49   | mm  | Main Thickness ; | 2.50     | mm           |
| Filling Depth :               | 7.50   | mm  | Current Cam :    | Cam C    |              |
| Main Air pressure :           | 0.814  | MPa |                  | 8.5-14mm |              |
| Oil Lubrication status :      |        |     |                  |          |              |
| Upper Punch Remain Time (S1): | 3      | Min |                  |          |              |
| Lower Punch Remain Time (S2): | 3      | Min |                  |          |              |
| Lower Head Remain Time (S3):  | 0      | Min |                  |          |              |
| Powder Status :               | Enable |     | Dust Collector : | Off      |              |
| Initial Reject :              | Off    |     | Buzzer :         | Off      |              |

### Tightness

|                  |           |      |    |             |    |
|------------------|-----------|------|----|-------------|----|
| Upper Punch :    | Average ; | 0.11 | kN |             |    |
|                  | Max ;     | 0.19 | kN | Max Punch ; | 28 |
| Lower Punch :    | Average ; | 0.07 | kN |             |    |
|                  | Max ;     | 0.09 | kN | Max Punch ; | 29 |
| Ejection Force : | Average ; | 0.03 | kN |             |    |
|                  | Max ;     | 0.19 | kN | Max Punch ; | 12 |

### Tablet Data (N/A)

|                 |                  |         |       |        |         |
|-----------------|------------------|---------|-------|--------|---------|
| Total Counter : | 1350728          | Tablets |       |        |         |
| A.W.C Counter : | 1345352          | Tablets |       |        |         |
| HEP :           | 24 (0.0%)        | Tablets | LEP : | 0 (0%) | Tablets |
| GOOD :          | 1345328 (100.0%) | Tablets |       |        |         |