

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	mr99799	Batch NO. :	EWM2510050
Print Interval :	50000 Tablets	Running Time :	21 Hour 19 Min 08 Sec
Total Counter :	3802036	Total Running Time :	1290 Hour 35 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	55	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		10.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	26.10	kN	No		
HEP :	25.0 %	25.10	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	20.48	kN	Yes 15	Times	
Ref :		20.08	kN			
LCP :	2.0 %	19.67	kN	Yes 15	Times	
LEP :	25.0 %	15.06	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	14.05	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.94	kN	Min :	2.76	kN	Punch NO.;	36
SD :	3.40	%	Max :	3.19	kN	Punch NO.;	51
Mean Main Pressure :	20.35	kN	Min :	18.53	kN	Punch NO.;	30
SD :	3.90	%	Max :	21.93	kN	Punch NO.;	13
Filling Depth :	Increase ;	1417	Times	Decrease ;	1415	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	15	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	6.46	mm	Pre Thickness ;	3.46	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.33	mm	Main Thickness ;	2.34	mm
Filling Depth :	7.71	mm	Current Cam :	Cam C	
Main Air pressure :	0.841	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	2	Min			
Lower Punch Remain Time (S2):	12	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.09	kN		
	Max ;	0.17	kN	Max Punch ;	29
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.09	kN	Max Punch ;	27
Ejection Force :	Average ;	0.02	kN		
	Max ;	0.11	kN	Max Punch ;	22

Tablet Data (N/A)

Total Counter :	3802036	Tablets			
A.W.C Counter :	3788957	Tablets			
HEP :	1861 (0.0%)	Tablets	LEP :	57 (0.0%)	Tablets
GOOD :	3787039 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	mr99799	Batch NO. :	EWM2510050
Print Interval :	50000 Tablets	Running Time :	21 Hour 19 Min 08 Sec
Total Counter :	3802036	Total Running Time :	1290 Hour 35 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	55	%	Manual ;	20	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		10.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	25.94	kN	No		
HEP :	25.0 %	24.94	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	20.35	kN	Yes 15	Times	
Ref :		19.95	kN			
LCP :	2.0 %	19.55	kN	Yes 15	Times	
LEP :	25.0 %	14.96	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	13.97	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.81	kN	Min :	2.49	kN	Punch NO.;	19
SD :	4.60	%	Max :	3.11	kN	Punch NO.;	48
Mean Main Pressure :	19.73	kN	Min :	18.02	kN	Punch NO.;	30
SD :	3.80	%	Max :	21.42	kN	Punch NO.;	53
Filling Depth :	Increase ;	752	Times	Decrease ;	557	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	15	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.40	mm	Pre Thickness ;	3.41	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.49	mm	Main Thickness ;	2.50	mm
Filling Depth :	7.54	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.841	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	2	Min			
Lower Punch Remain Time (S2):	12	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.09	kN		
	Max ;	0.17	kN	Max Punch ;	29
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.09	kN	Max Punch ;	27
Ejection Force :	Average ;	0.02	kN		
	Max ;	0.05	kN	Max Punch ;	25

Tablet Data (N/A)

Total Counter :	3802036	Tablets			
A.W.C Counter :	3788957	Tablets			
HEP :	1861 (0.0%)	Tablets	LEP :	57 (0.0%)	Tablets
GOOD :	3787039 (99.9%)	Tablets			