

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	pb97604	Batch NO. :	EWM2510250
Print Interval :	50000 Tablets	Running Time :	06 Hour 53 Min 36 Sec
Total Counter :	950414	Total Running Time :	1301 Hour 20 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	85	%	Manual ;	15	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		5	Min	Supply Time ;	5.0	Sec
Powder Supply Time :		10.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	28.59	kN	No		
HEP :	25.0 %	27.49	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	22.43	kN	Yes 15	Times	
Ref :		21.99	kN			
LCP :	2.0 %	21.55	kN	Yes 15	Times	
LEP :	25.0 %	16.49	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	15.39	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	3.29	kN	Min :	3.08	kN	Punch NO.;	18
		3.00	%	Max :	3.59	kN	Punch NO.;	3
Mean Main Pressure :	SD :	22.12	kN	Min :	21.03	kN	Punch NO.;	18
		2.70	%	Max :	23.74	kN	Punch NO.;	48
Filling Depth :	Increase ;	210	Times	Decrease ;	290	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	24	RPM	Capacity :	152640	Tablets/hour
Feeder : Status ;	Auto		Speed ;	20	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.32	mm	Pre Thickness ;	3.33	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.35	mm	Main Thickness ;	2.35	mm
Filling Depth :	7.76	mm	Current Cam :	Cam C	
Main Air pressure :	0.813	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	23	Min			
Lower Punch Remain Time (S2):	4	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.11	kN	Max Punch ;	16
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.17	kN	Max Punch ;	2

Tablet Data (N/A)

Total Counter :	950414	Tablets			
A.W.C Counter :	943353	Tablets			
HEP :	395 (0.0%)	Tablets	LEP :	351 (0.0%)	Tablets
GOOD :	942607 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	pb97604	Batch NO. :	EWM2510250
Print Interval :	50000 Tablets	Running Time :	06 Hour 53 Min 36 Sec
Total Counter :	950414	Total Running Time :	1301 Hour 20 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	80	%	Manual ;	20	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		5	Min	Supply Time ;	5.0	Sec
Powder Supply Time :		10.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	28.43	kN	No		
HEP :	25.0 %	27.34	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	22.31	kN	Yes 15	Times	
Ref :		21.87	kN			
LCP :	2.0 %	21.43	kN	Yes 15	Times	
LEP :	25.0 %	16.40	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	15.31	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	2.89	kN	Min :	2.62	kN	Punch NO.;	31
		4.50	%	Max :	3.23	kN	Punch NO.;	34
Mean Main Pressure :	SD :	21.65	kN	Min :	19.87	kN	Punch NO.;	31
		4.10	%	Max :	24.06	kN	Punch NO.;	40
Filling Depth :	Increase ;	342	Times	Decrease ;	363	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	24	RPM	Capacity :	152640	Tablets/hour
Feeder : Status ;	Auto		Speed ;	19	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.32	mm	Pre Thickness ;	3.33	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.40	mm	Main Thickness ;	2.40	mm
Filling Depth :	7.70	mm	Current Cam :	Cam C	
Main Air pressure :	0.813	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	23	Min			
Lower Punch Remain Time (S2):	4	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.11	kN	Max Punch ;	16
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.17	kN	Max Punch ;	2

Tablet Data (N/A)

Total Counter :	950414	Tablets			
A.W.C Counter :	943406	Tablets			
HEP :	395 (0.0%)	Tablets	LEP :	351 (0.0%)	Tablets
GOOD :	942660 (99.9%)	Tablets			