

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	pr190041	Batch NO. :	EWM2510450
Print Interval :	50000 Tablets	Running Time :	07 Hour 17 Min 41 Sec
Total Counter :	1300696	Total Running Time :	1331 Hour 53 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	100	%	Manual ;	15	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	29.94	kN	No		
HEP :	25.0 %	28.79	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	23.49	kN	Yes	15	Times
Ref :		23.03	kN			
LCP :	2.0 %	22.57	kN	Yes	15	Times
LEP :	25.0 %	17.27	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	16.12	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	3.38	kN	Min :	3.18	kN	Punch NO.;	35
SD :	2.90	%	Max :	3.61	kN	Punch NO.;	3
Mean Main Pressure :	22.85	kN	Min :	21.35	kN	Punch NO.;	35
SD :	2.90	%	Max :	24.19	kN	Punch NO.;	7
Filling Depth :	Increase ;	440	Times	Decrease ;	438	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	28	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.32	mm	Pre Thickness ;	3.33	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.35	mm	Main Thickness ;	2.36	mm
Filling Depth :	7.89	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.809	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	30	Min			
Lower Punch Remain Time (S2):	16	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.14	kN	Max Punch ;	22
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.18	kN	Max Punch ;	33

Tablet Data (N/A)

Total Counter :	1300696	Tablets			
A.W.C Counter :	1295680	Tablets			
HEP :	131 (0.0%)	Tablets	LEP :	158 (0.0%)	Tablets
GOOD :	1295391 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	pr190041	Batch NO. :	EWM2510450
Print Interval :	50000 Tablets	Running Time :	07 Hour 17 Min 41 Sec
Total Counter :	1300696	Total Running Time :	1331 Hour 53 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	86	%	Manual ;	20	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	29.23	kN	No		
HEP :	25.0 %	28.11	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	22.94	kN	Yes 15	Times	
Ref :		22.49	kN			
LCP :	2.0 %	22.04	kN	Yes 15	Times	
LEP :	25.0 %	16.87	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	15.74	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	3.03	kN	Min :	2.84	kN	Punch NO.;	46
		3.50	%	Max :	3.31	kN	Punch NO.;	17
Mean Main Pressure :		22.62	kN	Min :	20.85	kN	Punch NO.;	46
	SD :	4.30	%	Max :	25.33	kN	Punch NO.;	17
Filling Depth :	Increase ;	453	Times	Decrease ;	461	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	24	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.32	mm	Pre Thickness ;	3.33	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.43	mm	Main Thickness ;	2.43	mm
Filling Depth :	7.75	mm	Current Cam :	Cam C	
Main Air pressure :	0.809	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	30	Min			
Lower Punch Remain Time (S2):	16	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.14	kN	Max Punch ;	22
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.18	kN	Max Punch ;	33

Tablet Data (N/A)

Total Counter :	1300696	Tablets			
A.W.C Counter :	1295680	Tablets			
HEP :	131 (0.0%)	Tablets	LEP :	158 (0.0%)	Tablets
GOOD :	1295391 (100.0%)	Tablets			