

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	pb97604	Batch NO. :	EWM2510550
Print Interval :	50000 Tablets	Running Time :	04 Hour 45 Min 58 Sec
Total Counter :	850466	Total Running Time :	1354 Hour 33 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	106	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	30.04	kN	No		
HEP :	25.0 %	28.89	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	23.57	kN	Yes 15	Times	
Ref :		23.11	kN			
LCP :	2.0 %	22.65	kN	Yes 15	Times	
LEP :	25.0 %	17.33	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	16.18	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	3.43	kN	Min :	3.30	kN	Punch NO.;	27
SD :	2.50	%	Max :	3.66	kN	Punch NO.;	3
Mean Main Pressure :	22.82	kN	Min :	21.74	kN	Punch NO.;	37
SD :	2.70	%	Max :	24.38	kN	Punch NO.;	45
Filling Depth :	Increase ;	1312	Times	Decrease ;	1311	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	30	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.32	mm	Pre Thickness ;	3.33	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.38	mm	Main Thickness ;	2.39	mm
Filling Depth :	7.87	mm	Current Cam :	Cam C	
Main Air pressure :	0.806	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	14	Min			
Lower Punch Remain Time (S2):	13	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	On	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.14	kN	Max Punch ;	24
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.13	kN	Max Punch ;	33

Tablet Data (N/A)

Total Counter :	850466	Tablets			
A.W.C Counter :	848552	Tablets			
HEP :	14 (0.0%)	Tablets	LEP :	10 (0.0%)	Tablets
GOOD :	848528 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	pb97604	Batch NO. :	EWM2510550
Print Interval :	50000 Tablets	Running Time :	04 Hour 45 Min 58 Sec
Total Counter :	850466	Total Running Time :	1354 Hour 33 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	86	%	Manual ;	20	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	29.20	kN	No		
HEP :	25.0 %	28.07	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	22.91	kN	Yes 15	Times	
Ref :		22.46	kN			
LCP :	2.0 %	22.01	kN	Yes 15	Times	
LEP :	25.0 %	16.84	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	15.72	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	3.08	kN	Min :	2.91	kN	Punch NO.;	31
		3.60	%	Max :	3.38	kN	Punch NO.;	17
Mean Main Pressure :	SD :	22.59	kN	Min :	21.06	kN	Punch NO.;	37
		3.90	%	Max :	24.63	kN	Punch NO.;	34
Filling Depth :	Increase ;	833	Times	Decrease ;	875	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	24	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.32	mm	Pre Thickness ;	3.33	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.45	mm	Main Thickness ;	2.45	mm
Filling Depth :	7.61	mm	Current Cam :	Cam C	
Main Air pressure :	0.806	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	14	Min			
Lower Punch Remain Time (S2):	13	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	On	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.14	kN	Max Punch ;	24
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.13	kN	Max Punch ;	33

Tablet Data (N/A)

Total Counter :	850466	Tablets			
A.W.C Counter :	848552	Tablets			
HEP :	14 (0.0%)	Tablets	LEP :	10 (0.0%)	Tablets
GOOD :	848528 (100.0%)	Tablets			