

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	pb97604	Batch NO. :	EWM2511150
Print Interval :	50000 Tablets	Running Time :	12 Hour 53 Min 58 Sec
Total Counter :	2301172	Total Running Time :	1438 Hour 21 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	89	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	0.5	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	29.87	kN	No		
HEP :	25.0 %	28.72	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	23.44	kN	Yes	15	Times
Ref :		22.98	kN			
LCP :	2.0 %	22.52	kN	Yes	15	Times
LEP :	25.0 %	17.23	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	16.08	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	3.62	kN	Min :	3.47	kN	Punch NO.;	27
		2.20	%	Max :	3.86	kN	Punch NO.;	45
Mean Main Pressure :	SD :	23.28	kN	Min :	22.31	kN	Punch NO.;	27
		2.40	%	Max :	24.99	kN	Punch NO.;	45
Filling Depth :	Increase ;	783	Times	Decrease ;	820	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	25	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.32	mm	Pre Thickness ;	3.33	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.38	mm	Main Thickness ;	2.39	mm
Filling Depth :	7.94	mm	Current Cam :	Cam C	
Main Air pressure :	0.788	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	21	Min			
Lower Punch Remain Time (S2):	24	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.12	kN	Max Punch ;	19
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.19	kN	Max Punch ;	13

Tablet Data (N/A)

Total Counter :	2301172	Tablets			
A.W.C Counter :	2297695	Tablets			
HEP :	173 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	2297522 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	pb97604	Batch NO. :	EWM2511150
Print Interval :	50000 Tablets	Running Time :	12 Hour 53 Min 58 Sec
Total Counter :	2301172	Total Running Time :	1438 Hour 21 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	72	%	Manual ;	20	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	0.5	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	28.52	kN	No		
HEP :	25.0 %	27.42	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	22.38	kN	Yes	15	Times
Ref :		21.94	kN			
LCP :	2.0 %	21.50	kN	Yes	15	Times
LEP :	25.0 %	16.45	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	15.36	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	3.09	kN	Min :	2.84	kN	Punch NO.;	52
		3.70	%	Max :	3.42	kN	Punch NO.;	45
Mean Main Pressure :	SD :	21.57	kN	Min :	19.91	kN	Punch NO.;	52
		3.60	%	Max :	23.38	kN	Punch NO.;	45
Filling Depth :	Increase ;	455	Times	Decrease ;	485	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	20	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.32	mm	Pre Thickness ;	3.33	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.46	mm	Main Thickness ;	2.47	mm
Filling Depth :	7.37	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.788	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	21	Min			
Lower Punch Remain Time (S2):	24	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.12	kN	Max Punch ;	18
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.15	kN	Max Punch ;	13

Tablet Data (N/A)

Total Counter :	2301172	Tablets			
A.W.C Counter :	2297695	Tablets			
HEP :	173 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	2297522 (100.0%)	Tablets			