

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	rp98927	Batch NO. :	EWM2511250
Print Interval :	50000 Tablets	Running Time :	12 Hour 53 Min 55 Sec
Total Counter :	2301126	Total Running Time :	1463 Hour 32 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	90	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	0.5	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	29.53	kN	No		
HEP :	25.0 %	28.39	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	23.17	kN	Yes 15	Times	
Ref :		22.71	kN			
LCP :	2.0 %	22.26	kN	Yes 15	Times	
LEP :	25.0 %	17.03	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	15.90	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	3.50	kN	Min :	3.32	kN	Punch NO.;	22
SD :	2.10	%	Max :	3.77	kN	Punch NO.;	45
Mean Main Pressure :	22.91	kN	Min :	21.69	kN	Punch NO.;	22
SD :	2.20	%	Max :	24.48	kN	Punch NO.;	45
Filling Depth :	Increase ; 152	Times	Decrease ; 200	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	25	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.32	mm	Pre Thickness ;	3.33	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.38	mm	Main Thickness ;	2.39	mm
Filling Depth :	7.91	mm	Current Cam :	Cam C	
Main Air pressure :	0.785	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	38	Min			
Lower Punch Remain Time (S2):	21	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.03	kN	Max Punch ;	29
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.14	kN	Max Punch ;	23
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.19	kN	Max Punch ;	26

Tablet Data (N/A)

Total Counter :	2301126	Tablets			
A.W.C Counter :	2296286	Tablets			
HEP :	94 (0.0%)	Tablets	LEP :	4 (0.0%)	Tablets
GOOD :	2296188 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	rp98927	Batch NO. :	EWM2511250
Print Interval :	50000 Tablets	Running Time :	12 Hour 53 Min 55 Sec
Total Counter :	2301126	Total Running Time :	1463 Hour 32 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	72	%	Manual ;	20	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	0.5	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	27.69	kN	No		
HEP :	25.0 %	26.63	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	21.73	kN	Yes 15	Times	
Ref :		21.30	kN			
LCP :	2.0 %	20.88	kN	Yes 15	Times	
LEP :	25.0 %	15.98	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	14.91	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	3.00	kN	Min :	2.80	kN	Punch NO.;	1
SD :	2.90	%	Max :	3.31	kN	Punch NO.;	45
Mean Main Pressure :	21.47	kN	Min :	19.48	kN	Punch NO.;	1
SD :	3.30	%	Max :	23.75	kN	Punch NO.;	45
Filling Depth :	Increase ;	132	Times	Decrease ;	142	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	20	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.32	mm	Pre Thickness ;	3.33	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.46	mm	Main Thickness ;	2.47	mm
Filling Depth :	7.28	mm	Current Cam :	Cam C	
Main Air pressure :	0.785	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	38	Min			
Lower Punch Remain Time (S2):	21	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.03	kN	Max Punch ;	29
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.14	kN	Max Punch ;	23
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.19	kN	Max Punch ;	26

Tablet Data (N/A)

Total Counter :	2301126	Tablets			
A.W.C Counter :	2296286	Tablets			
HEP :	94 (0.0%)	Tablets	LEP :	4 (0.0%)	Tablets
GOOD :	2296188 (100.0%)	Tablets			