

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	rp98927	Batch NO. :	EWM2511550
Print Interval :	50000 Tablets	Running Time :	02 Hour 14 Min 43 Sec
Total Counter :	400198	Total Running Time :	1478 Hour 2 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	100	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	0.5	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	11.82	kN	No		
HEP :	25.0 %	11.36	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	9.27	kN	Yes 15	Times	
Ref :		9.09	kN			
LCP :	2.0 %	8.91	kN	Yes 15	Times	
LEP :	25.0 %	6.82	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	6.36	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.68	kN	Min :	2.46	kN	Punch NO.;	13
SD :	3.70	%	Max :	3.03	kN	Punch NO.;	45
Mean Main Pressure :	9.29	kN	Min :	8.08	kN	Punch NO.;	35
SD :	5.50	%	Max :	10.96	kN	Punch NO.;	45
Filling Depth :	Increase ;	303	Times	Decrease ;	367	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	28	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.32	mm	Pre Thickness ;	3.33	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.41	mm	Main Thickness ;	2.42	mm
Filling Depth :	7.19	mm	Current Cam :	Cam C	
Main Air pressure :	0.776	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	16	Min			
Lower Punch Remain Time (S2):	39	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.14	kN	Max Punch ;	29
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.15	kN	Max Punch ;	23
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.13	kN	Max Punch ;	24

Tablet Data (N/A)

Total Counter :	400198	Tablets			
A.W.C Counter :	391814	Tablets			
HEP :	315 (0.1%)	Tablets	LEP :	72 (0.0%)	Tablets
GOOD :	391427 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	rp98927	Batch NO. :	EWM2511550
Print Interval :	50000 Tablets	Running Time :	02 Hour 14 Min 43 Sec
Total Counter :	400198	Total Running Time :	1478 Hour 2 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	100	%	Manual ;	20	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	0.5	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	11.61	kN	No		
HEP :	25.0 %	11.17	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	9.11	kN	Yes 15	Times	
Ref :		8.93	kN			
LCP :	2.0 %	8.76	kN	Yes 15	Times	
LEP :	25.0 %	6.70	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	6.25	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.80	kN	Min :	1.55	kN	Punch NO.;	44
SD :	7.30	%	Max :	2.12	kN	Punch NO.;	14
Mean Main Pressure :	8.93	kN	Min :	7.57	kN	Punch NO.;	44
SD :	7.30	%	Max :	10.30	kN	Punch NO.;	14
Filling Depth :	Increase ;	304	Times	Decrease ;	323	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	28	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.32	mm	Pre Thickness ;	3.33	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.46	mm	Main Thickness ;	2.47	mm
Filling Depth :	6.72	mm	Current Cam :	Cam C	
Main Air pressure :	0.776	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	16	Min			
Lower Punch Remain Time (S2):	39	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.14	kN	Max Punch ;	29
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.15	kN	Max Punch ;	23
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.18	kN	Max Punch ;	25

Tablet Data (N/A)

Total Counter :	400198	Tablets			
A.W.C Counter :	391814	Tablets			
HEP :	315 (0.1%)	Tablets	LEP :	72 (0.0%)	Tablets
GOOD :	391427 (99.9%)	Tablets			