

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	rp98927	Batch NO. :	EWM2511550
Print Interval :	50000 Tablets	Running Time :	02 Hour 48 Min 23 Sec
Total Counter :	500254	Total Running Time :	1478 Hour 35 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	100	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	0.5	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	11.82	kN	No		
HEP :	25.0 %	11.36	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	9.27	kN	Yes 15	Times	
Ref :		9.09	kN			
LCP :	2.0 %	8.91	kN	Yes 15	Times	
LEP :	25.0 %	6.82	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	6.36	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.63	kN	Min :	2.46	kN	Punch NO.;	27
SD :	4.10	%	Max :	3.01	kN	Punch NO.;	25
Mean Main Pressure :	9.10	kN	Min :	8.10	kN	Punch NO.;	47
SD :	6.50	%	Max :	11.15	kN	Punch NO.;	25
Filling Depth :	Increase ;	315	Times	Decrease ;	380	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	28	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.32	mm	Pre Thickness ;	3.33	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.41	mm	Main Thickness ;	2.42	mm
Filling Depth :	7.16	mm	Current Cam :	Cam C	
Main Air pressure :	0.746	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	43	Min			
Lower Punch Remain Time (S2):	6	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.02	kN		
	Max ;	0.10	kN	Max Punch ;	29
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.15	kN	Max Punch ;	23
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.18	kN	Max Punch ;	25

Tablet Data (N/A)

Total Counter :	500254	Tablets			
A.W.C Counter :	491825	Tablets			
HEP :	360 (0.1%)	Tablets	LEP :	79 (0.0%)	Tablets
GOOD :	491386 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	rp98927	Batch NO. :	EWM2511550
Print Interval :	50000 Tablets	Running Time :	02 Hour 48 Min 23 Sec
Total Counter :	500254	Total Running Time :	1478 Hour 35 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	100	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	0.5	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	11.61	kN	No		
HEP :	25.0 %	11.17	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	9.11	kN	Yes 15	Times	
Ref :		8.93	kN			
LCP :	2.0 %	8.76	kN	Yes 15	Times	
LEP :	25.0 %	6.70	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	6.25	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.78	kN	Min :	1.55	kN	Punch NO.;	22
SD :	6.70	%	Max :	2.12	kN	Punch NO.;	53
Mean Main Pressure :	8.92	kN	Min :	7.72	kN	Punch NO.;	46
SD :	6.60	%	Max :	10.25	kN	Punch NO.;	45
Filling Depth :	Increase ;	322	Times	Decrease ;	342	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	28	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.32	mm	Pre Thickness ;	3.33	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.46	mm	Main Thickness ;	2.47	mm
Filling Depth :	6.69	mm	Current Cam :	Cam C	
Main Air pressure :	0.746	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	43	Min			
Lower Punch Remain Time (S2):	6	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.02	kN		
	Max ;	0.12	kN	Max Punch ;	29
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.15	kN	Max Punch ;	23
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.18	kN	Max Punch ;	25

Tablet Data (N/A)

Total Counter :	500254	Tablets			
A.W.C Counter :	491825	Tablets			
HEP :	360 (0.1%)	Tablets	LEP :	79 (0.0%)	Tablets
GOOD :	491386 (99.9%)	Tablets			