

## PRODUCTION REPORT

### Product Information

|                  |               |                      |                        |
|------------------|---------------|----------------------|------------------------|
| Machine Name :   | VANTIX P720D  | Product Name :       | MET 500<br>MG,STEW1A00 |
| User ID :        | rp98927       | Batch NO. :          | EWM2511550             |
| Print Interval : | 50000 Tablets | Running Time :       | 03 Hour 38 Min 53 Sec  |
| Total Counter :  | 650364        | Total Running Time : | 1479 Hour 26 Min       |
| Station :        | Station 1     |                      |                        |

### Setting Value

|                                    |        |           |         |                    |              |           |
|------------------------------------|--------|-----------|---------|--------------------|--------------|-----------|
| Feeder :                           | Auto ; | 100       | %       | Manual ;           | 15           | RPM       |
| Filling Cam :                      |        | Cam C     |         | Cam Range :        | Min :        | 6.50 mm   |
|                                    |        | 8.5-14mm  |         |                    | Max :        | 12.00 mm  |
| Target Quantity :                  |        | 4500000   | Tablets |                    |              |           |
| Air Pressure Low Limit :           |        | 0.600     | MPa     |                    |              |           |
| Oil Lubrication :                  |        |           |         |                    |              |           |
| Upper Punch Interval Time(S1) ;    |        | 60        | Min     | Supply Time ;      | 0.2          | Sec       |
| Lower Punch Interval Time(S2) ;    |        | 40        | Min     | Supply Time ;      | 0.5          | Sec       |
| Powder Supply Time :               |        | 30.0      | Sec     |                    |              |           |
| Initial Reject Time :              |        | 1         | Tablets |                    |              |           |
| Upper Punch Tightness High Limit : |        | 1.00      | kN      |                    |              |           |
| Lower Punch Tightness High Limit : |        | 4.00      | kN      |                    |              |           |
| Ejecting Force High Limit :        |        | 4.00      | kN      |                    |              |           |
|                                    |        |           |         | Stop Condition ;   |              |           |
| HSP :                              | 30.0 % | 11.82     | kN      | No                 |              |           |
| HEP :                              | 25.0 % | 11.36     | kN      | Yes 10             | Rotations 15 | Tablets   |
| HCP :                              | 2.0 %  | 9.27      | kN      | Yes 15             | Times        |           |
| Ref :                              |        | 9.09      | kN      |                    |              |           |
| LCP :                              | 2.0 %  | 8.91      | kN      | Yes 15             | Times        |           |
| LEP :                              | 25.0 % | 6.82      | kN      | Yes 10             | Rotations 15 | Tablets   |
| LSP :                              | 30.0 % | 6.36      | kN      | No                 |              |           |
| SD limit :                         | 35.0 % |           |         | Yes                |              |           |
| Pre HSP                            |        | 30.00     | kN      | Yes                |              |           |
| Mean Calculation range :           | 2      | Rotations |         | Calculation Pass : | 2            | Rotations |
| Empty Punch No. :                  | None   |           |         |                    |              |           |

### Pressure Data

|                      |            |     |       |            |     |            |    |
|----------------------|------------|-----|-------|------------|-----|------------|----|
| Mean Pre Pressure :  | 2.64       | kN  | Min : | 2.41       | kN  | Punch NO.; | 35 |
| SD :                 | 4.50       | %   | Max : | 3.07       | kN  | Punch NO.; | 45 |
| Mean Main Pressure : | 9.23       | kN  | Min : | 7.86       | kN  | Punch NO.; | 35 |
| SD :                 | 6.40       | %   | Max : | 11.11      | kN  | Punch NO.; | 45 |
| Filling Depth :      | Increase ; | 349 | Times | Decrease ; | 411 | Times      |    |

## PRODUCTION REPORT

### Operation Value

|                               |        |     |                  |          |              |
|-------------------------------|--------|-----|------------------|----------|--------------|
| Disk Speed :                  | 28     | RPM | Capacity :       | 178080   | Tablets/hour |
| Feeder : Status ;             | Auto   |     | Speed ;          | 28       | RPM          |
| Pre Upper Punch Position ;    | 2.99   | mm  |                  |          |              |
| Pre Lower Punch Position ;    | 6.32   | mm  | Pre Thickness ;  | 3.33     | mm           |
| Main Upper Punch Position ;   | 2.99   | mm  |                  |          |              |
| Main Lower Punch Position ;   | 5.41   | mm  | Main Thickness ; | 2.42     | mm           |
| Filling Depth :               | 7.20   | mm  | Current Cam :    | Cam C    |              |
| Main Air pressure :           | 0.770  | MPa |                  | 8.5-14mm |              |
| Oil Lubrication status :      |        |     |                  |          |              |
| Upper Punch Remain Time (S1): | 53     | Min |                  |          |              |
| Lower Punch Remain Time (S2): | 36     | Min |                  |          |              |
| Lower Head Remain Time (S3):  | 0      | Min |                  |          |              |
| Powder Status :               | Enable |     | Dust Collector : | Off      |              |
| Initial Reject :              | Off    |     | Buzzer :         | Off      |              |

### Tightness

|                  |           |      |    |             |    |
|------------------|-----------|------|----|-------------|----|
| Upper Punch :    | Average ; | 0.02 | kN |             |    |
|                  | Max ;     | 0.11 | kN | Max Punch ; | 29 |
| Lower Punch :    | Average ; | 0.10 | kN |             |    |
|                  | Max ;     | 0.16 | kN | Max Punch ; | 23 |
| Ejection Force : | Average ; | 0.04 | kN |             |    |
|                  | Max ;     | 0.19 | kN | Max Punch ; | 26 |

### Tablet Data (N/A)

|                 |                   |         |       |           |         |
|-----------------|-------------------|---------|-------|-----------|---------|
| Total Counter : | 650364            | Tablets |       |           |         |
| A.W.C Counter : | 641974            | Tablets |       |           |         |
| HEP :           | 455 (0.1%)        | Tablets | LEP : | 93 (0.0%) | Tablets |
| GOOD :          | 641426<br>(99.9%) | Tablets |       |           |         |

## PRODUCTION REPORT

### Product Information

|                  |               |                      |                        |
|------------------|---------------|----------------------|------------------------|
| Machine Name :   | VANTIX P720D  | Product Name :       | MET 500<br>MG,STEW1A00 |
| User ID :        | rp98927       | Batch NO. :          | EWM2511550             |
| Print Interval : | 50000 Tablets | Running Time :       | 03 Hour 38 Min 53 Sec  |
| Total Counter :  | 650364        | Total Running Time : | 1479 Hour 26 Min       |
| Station :        | Station 2     |                      |                        |

### Setting Value

|                                    |        |                   |         |                    |              |           |
|------------------------------------|--------|-------------------|---------|--------------------|--------------|-----------|
| Feeder :                           | Auto ; | 100               | %       | Manual ;           | 20           | RPM       |
| Filling Cam :                      |        | Cam C<br>8.5-14mm |         | Cam Range :        | Min :        | 6.50 mm   |
| Target Quantity :                  |        | 4500000           | Tablets |                    | Max :        | 12.00 mm  |
| Air Pressure Low Limit :           |        | 0.600             | MPa     |                    |              |           |
| Oil Lubrication :                  |        |                   |         |                    |              |           |
| Upper Punch Interval Time(S1) ;    |        | 60                | Min     | Supply Time ;      | 0.2          | Sec       |
| Lower Punch Interval Time(S2) ;    |        | 40                | Min     | Supply Time ;      | 0.5          | Sec       |
| Powder Supply Time :               |        | 30.0              | Sec     |                    |              |           |
| Initial Reject Time :              |        | 1                 | Tablets |                    |              |           |
| Upper Punch Tightness High Limit : |        | 1.00              | kN      |                    |              |           |
| Lower Punch Tightness High Limit : |        | 4.00              | kN      |                    |              |           |
| Ejecting Force High Limit :        |        | 4.00              | kN      |                    |              |           |
|                                    |        |                   |         | Stop Condition ;   |              |           |
| HSP :                              | 30.0 % | 11.61             | kN      | No                 |              |           |
| HEP :                              | 25.0 % | 11.17             | kN      | Yes 10             | Rotations 15 | Tablets   |
| HCP :                              | 2.0 %  | 9.11              | kN      | Yes 15             | Times        |           |
| Ref :                              |        | 8.93              | kN      |                    |              |           |
| LCP :                              | 2.0 %  | 8.76              | kN      | Yes 15             | Times        |           |
| LEP :                              | 25.0 % | 6.70              | kN      | Yes 10             | Rotations 15 | Tablets   |
| LSP :                              | 30.0 % | 6.25              | kN      | No                 |              |           |
| SD limit :                         | 35.0 % |                   |         | Yes                |              |           |
| Pre HSP                            |        | 30.00             | kN      | Yes                |              |           |
| Mean Calculation range :           | 2      | Rotations         |         | Calculation Pass : | 2            | Rotations |
| Empty Punch No. :                  | N      |                   |         |                    |              |           |

### Pressure Data

|                      |            |     |       |            |     |            |    |
|----------------------|------------|-----|-------|------------|-----|------------|----|
| Mean Pre Pressure :  | 1.74       | kN  | Min : | 1.51       | kN  | Punch NO.; | 44 |
| SD :                 | 6.40       | %   | Max : | 2.04       | kN  | Punch NO.; | 14 |
| Mean Main Pressure : | 8.91       | kN  | Min : | 7.72       | kN  | Punch NO.; | 35 |
| SD :                 | 6.40       | %   | Max : | 10.14      | kN  | Punch NO.; | 24 |
| Filling Depth :      | Increase ; | 343 | Times | Decrease ; | 363 | Times      |    |

## PRODUCTION REPORT

### Operation Value

|                               |        |     |                  |          |              |
|-------------------------------|--------|-----|------------------|----------|--------------|
| Disk Speed :                  | 28     | RPM | Capacity :       | 178080   | Tablets/hour |
| Feeder : Status ;             | Auto   |     | Speed ;          | 28       | RPM          |
| Pre Upper Punch Position ;    | 2.99   | mm  |                  |          |              |
| Pre Lower Punch Position ;    | 6.32   | mm  | Pre Thickness ;  | 3.33     | mm           |
| Main Upper Punch Position ;   | 2.99   | mm  |                  |          |              |
| Main Lower Punch Position ;   | 5.46   | mm  | Main Thickness ; | 2.47     | mm           |
| Filling Depth :               | 6.69   | mm  | Current Cam :    | Cam C    |              |
| Main Air pressure :           | 0.770  | MPa |                  | 8.5-14mm |              |
| Oil Lubrication status :      |        |     |                  |          |              |
| Upper Punch Remain Time (S1): | 53     | Min |                  |          |              |
| Lower Punch Remain Time (S2): | 36     | Min |                  |          |              |
| Lower Head Remain Time (S3):  | 0      | Min |                  |          |              |
| Powder Status :               | Enable |     | Dust Collector : | Off      |              |
| Initial Reject :              | Off    |     | Buzzer :         | Off      |              |

### Tightness

|                  |           |      |    |             |    |
|------------------|-----------|------|----|-------------|----|
| Upper Punch :    | Average ; | 0.02 | kN |             |    |
|                  | Max ;     | 0.11 | kN | Max Punch ; | 29 |
| Lower Punch :    | Average ; | 0.11 | kN |             |    |
|                  | Max ;     | 0.15 | kN | Max Punch ; | 23 |
| Ejection Force : | Average ; | 0.04 | kN |             |    |
|                  | Max ;     | 0.18 | kN | Max Punch ; | 25 |

### Tablet Data (N/A)

|                 |                   |         |       |           |         |
|-----------------|-------------------|---------|-------|-----------|---------|
| Total Counter : | 650364            | Tablets |       |           |         |
| A.W.C Counter : | 641974            | Tablets |       |           |         |
| HEP :           | 455 (0.1%)        | Tablets | LEP : | 93 (0.0%) | Tablets |
| GOOD :          | 641426<br>(99.9%) | Tablets |       |           |         |