

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	pb97604	Batch NO. :	EWM2511550
Print Interval :	50000 Tablets	Running Time :	18 Hour 30 Min 53 Sec
Total Counter :	3302012	Total Running Time :	1494 Hour 19 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	100	%	Manual ;	15	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		70	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.5	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	12.40	kN	No		
HEP :	25.0 %	11.93	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	9.73	kN	Yes 15	Times	
Ref :		9.54	kN			
LCP :	2.0 %	9.35	kN	Yes 15	Times	
LEP :	25.0 %	7.16	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	6.68	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.93	kN	Min :	1.78	kN	Punch NO.;	48
SD :	3.70	%	Max :	2.12	kN	Punch NO.;	45
Mean Main Pressure :	9.44	kN	Min :	8.28	kN	Punch NO.;	48
SD :	6.10	%	Max :	10.79	kN	Punch NO.;	25
Filling Depth :	Increase ;	808	Times	Decrease ;	895	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	28	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.53	mm	Pre Thickness ;	3.54	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.41	mm	Main Thickness ;	2.42	mm
Filling Depth :	7.17	mm	Current Cam :	Cam C	
Main Air pressure :	0.806	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	43	Min			
Lower Punch Remain Time (S2):	26	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.10	kN	Max Punch ;	29
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.17	kN	Max Punch ;	35
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.08	kN	Max Punch ;	35

Tablet Data (N/A)

Total Counter :	3302012	Tablets			
A.W.C Counter :	3292608	Tablets			
HEP :	1925 (0.1%)	Tablets	LEP :	207 (0.0%)	Tablets
GOOD :	3290476 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	pb97604	Batch NO. :	EWM2511550
Print Interval :	50000 Tablets	Running Time :	18 Hour 30 Min 53 Sec
Total Counter :	3302012	Total Running Time :	1494 Hour 19 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	100	%	Manual ;	20	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		70	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.5	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	11.72	kN	No		
HEP :	25.0 %	11.27	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	9.20	kN	Yes 15	Times	
Ref :		9.02	kN			
LCP :	2.0 %	8.84	kN	Yes 15	Times	
LEP :	25.0 %	6.76	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	6.31	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.78	kN	Min :	1.63	kN	Punch NO.;	32
SD :	5.40	%	Max :	2.04	kN	Punch NO.;	4
Mean Main Pressure :	9.11	kN	Min :	8.05	kN	Punch NO.;	32
SD :	6.20	%	Max :	10.50	kN	Punch NO.;	4
Filling Depth :	Increase ;	601	Times	Decrease ;	628	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	28	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.32	mm	Pre Thickness ;	3.33	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.46	mm	Main Thickness ;	2.47	mm
Filling Depth :	6.66	mm	Current Cam :	Cam C	
Main Air pressure :	0.806	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	43	Min			
Lower Punch Remain Time (S2):	26	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.08	kN	Max Punch ;	29
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.17	kN	Max Punch ;	35
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.08	kN	Max Punch ;	35

Tablet Data (N/A)

Total Counter :	3302012	Tablets			
A.W.C Counter :	3292608	Tablets			
HEP :	1925 (0.1%)	Tablets	LEP :	207 (0.0%)	Tablets
GOOD :	3290476 (99.9%)	Tablets			