

## PRODUCTION REPORT

### Product Information

|                  |               |                      |                        |
|------------------|---------------|----------------------|------------------------|
| Machine Name :   | VANTIX P720D  | Product Name :       | MET 500<br>MG,STEW1A00 |
| User ID :        | pb97604       | Batch NO. :          | EWM2512250             |
| Print Interval : | 50000 Tablets | Running Time :       | 05 Hour 20 Min 38 Sec  |
| Total Counter :  | 950454        | Total Running Time : | 1506 Hour 9 Min        |
| Station :        | Station 1     |                      |                        |

### Setting Value

|                                    |        |                   |         |                    |              |           |
|------------------------------------|--------|-------------------|---------|--------------------|--------------|-----------|
| Feeder :                           | Auto ; | 105               | %       | Manual ;           | 15           | RPM       |
| Filling Cam :                      |        | Cam C<br>8.5-14mm |         | Cam Range :        | Min :        | 6.50 mm   |
| Target Quantity :                  |        | 4500000           | Tablets |                    | Max :        | 12.00 mm  |
| Air Pressure Low Limit :           |        | 0.400             | MPa     |                    |              |           |
| Oil Lubrication :                  |        |                   |         |                    |              |           |
| Upper Punch Interval Time(S1) ;    |        | 70                | Min     | Supply Time ;      | 0.1          | Sec       |
| Lower Punch Interval Time(S2) ;    |        | 60                | Min     | Supply Time ;      | 0.2          | Sec       |
| Powder Supply Time :               |        | 30.0              | Sec     |                    |              |           |
| Initial Reject Time :              |        | 1                 | Tablets |                    |              |           |
| Upper Punch Tightness High Limit : |        | 1.00              | kN      |                    |              |           |
| Lower Punch Tightness High Limit : |        | 4.00              | kN      |                    |              |           |
| Ejecting Force High Limit :        |        | 4.00              | kN      |                    |              |           |
|                                    |        |                   |         | Stop Condition ;   |              |           |
| HSP :                              | 30.0 % | 26.99             | kN      | No                 |              |           |
| HEP :                              | 25.0 % | 25.95             | kN      | Yes 10             | Rotations 15 | Tablets   |
| HCP :                              | 2.0 %  | 21.18             | kN      | Yes 15             | Times        |           |
| Ref :                              |        | 20.76             | kN      |                    |              |           |
| LCP :                              | 2.0 %  | 20.35             | kN      | Yes 15             | Times        |           |
| LEP :                              | 25.0 % | 15.57             | kN      | Yes 10             | Rotations 15 | Tablets   |
| LSP :                              | 30.0 % | 14.53             | kN      | No                 |              |           |
| SD limit :                         | 35.0 % |                   |         | Yes                |              |           |
| Pre HSP                            |        | 30.00             | kN      | Yes                |              |           |
| Mean Calculation range :           | 2      | Rotations         |         | Calculation Pass : | 2            | Rotations |
| Empty Punch No. :                  | None   |                   |         |                    |              |           |

### Pressure Data

|                      |            |    |       |            |    |            |    |
|----------------------|------------|----|-------|------------|----|------------|----|
| Mean Pre Pressure :  | 2.89       | kN | Min : | 2.85       | kN | Punch NO.; | 30 |
| SD :                 | 0.90       | %  | Max : | 2.97       | kN | Punch NO.; | 11 |
| Mean Main Pressure : | 21.20      | kN | Min : | 20.22      | kN | Punch NO.; | 30 |
| SD :                 | 2.50       | %  | Max : | 22.63      | kN | Punch NO.; | 11 |
| Filling Depth :      | Increase ; | 77 | Times | Decrease ; | 89 | Times      |    |

## PRODUCTION REPORT

### Operation Value

|                               |         |     |                  |          |              |
|-------------------------------|---------|-----|------------------|----------|--------------|
| Disk Speed :                  | 28      | RPM | Capacity :       | 178080   | Tablets/hour |
| Feeder : Status ;             | Auto    |     | Speed ;          | 29       | RPM          |
| Pre Upper Punch Position ;    | 2.99    | mm  |                  |          |              |
| Pre Lower Punch Position ;    | 7.00    | mm  | Pre Thickness ;  | 4.01     | mm           |
| Main Upper Punch Position ;   | 2.99    | mm  |                  |          |              |
| Main Lower Punch Position ;   | 5.60    | mm  | Main Thickness ; | 2.61     | mm           |
| Filling Depth :               | 8.23    | mm  | Current Cam :    | Cam C    |              |
| Main Air pressure :           | 0.801   | MPa |                  | 8.5-14mm |              |
| Oil Lubrication status :      |         |     |                  |          |              |
| Upper Punch Remain Time (S1): | 5       | Min |                  |          |              |
| Lower Punch Remain Time (S2): | 29      | Min |                  |          |              |
| Lower Head Remain Time (S3):  | 0       | Min |                  |          |              |
| Powder Status :               | Disable |     | Dust Collector : | Off      |              |
| Initial Reject :              | Off     |     | Buzzer :         | Off      |              |

### Tightness

|                  |           |      |    |             |    |
|------------------|-----------|------|----|-------------|----|
| Upper Punch :    | Average ; | 0.03 | kN |             |    |
|                  | Max ;     | 0.10 | kN | Max Punch ; | 45 |
| Lower Punch :    | Average ; | 0.10 | kN |             |    |
|                  | Max ;     | 0.15 | kN | Max Punch ; | 24 |
| Ejection Force : | Average ; | 0.03 | kN |             |    |
|                  | Max ;     | 0.06 | kN | Max Punch ; | 12 |

### Tablet Data (N/A)

|                 |                   |         |       |            |         |
|-----------------|-------------------|---------|-------|------------|---------|
| Total Counter : | 950454            | Tablets |       |            |         |
| A.W.C Counter : | 944610            | Tablets |       |            |         |
| HEP :           | 61 (0.0%)         | Tablets | LEP : | 629 (0.1%) | Tablets |
| GOOD :          | 943920<br>(99.9%) | Tablets |       |            |         |

## PRODUCTION REPORT

### Product Information

|                  |               |                      |                        |
|------------------|---------------|----------------------|------------------------|
| Machine Name :   | VANTIX P720D  | Product Name :       | MET 500<br>MG,STEW1A00 |
| User ID :        | pb97604       | Batch NO. :          | EWM2512250             |
| Print Interval : | 50000 Tablets | Running Time :       | 05 Hour 20 Min 38 Sec  |
| Total Counter :  | 950454        | Total Running Time : | 1506 Hour 9 Min        |
| Station :        | Station 2     |                      |                        |

### Setting Value

|                                    |        |                   |         |                    |       |                      |
|------------------------------------|--------|-------------------|---------|--------------------|-------|----------------------|
| Feeder :                           | Auto ; | 100               | %       | Manual ;           | 20    | RPM                  |
| Filling Cam :                      |        | Cam C<br>8.5-14mm |         | Cam Range :        | Min : | 6.50 mm              |
| Target Quantity :                  |        | 4500000           | Tablets |                    | Max : | 12.00 mm             |
| Air Pressure Low Limit :           |        | 0.400             | MPa     |                    |       |                      |
| Oil Lubrication :                  |        |                   |         |                    |       |                      |
| Upper Punch Interval Time(S1) ;    |        | 70                | Min     | Supply Time ;      | 0.1   | Sec                  |
| Lower Punch Interval Time(S2) ;    |        | 60                | Min     | Supply Time ;      | 0.2   | Sec                  |
| Powder Supply Time :               |        | 30.0              | Sec     |                    |       |                      |
| Initial Reject Time :              |        | 1                 | Tablets |                    |       |                      |
| Upper Punch Tightness High Limit : |        | 1.00              | kN      |                    |       |                      |
| Lower Punch Tightness High Limit : |        | 4.00              | kN      |                    |       |                      |
| Ejecting Force High Limit :        |        | 4.00              | kN      |                    |       |                      |
|                                    |        |                   |         | Stop Condition ;   |       |                      |
| HSP :                              | 30.0 % | 30.22             | kN      | No                 |       |                      |
| HEP :                              | 25.0 % | 29.06             | kN      | Yes                | 10    | Rotations 15 Tablets |
| HCP :                              | 2.0 %  | 23.71             | kN      | Yes                | 15    | Times                |
| Ref :                              |        | 23.25             | kN      |                    |       |                      |
| LCP :                              | 2.0 %  | 22.78             | kN      | Yes                | 15    | Times                |
| LEP :                              | 25.0 % | 17.43             | kN      | Yes                | 10    | Rotations 15 Tablets |
| LSP :                              | 30.0 % | 16.27             | kN      | No                 |       |                      |
| SD limit :                         | 35.0 % |                   |         | Yes                |       |                      |
| Pre HSP                            |        | 30.00             | kN      | Yes                |       |                      |
| Mean Calculation range :           | 2      | Rotations         |         | Calculation Pass : | 2     | Rotations            |
| Empty Punch No. :                  | N      |                   |         |                    |       |                      |

### Pressure Data

|                      |            |    |       |            |    |            |    |
|----------------------|------------|----|-------|------------|----|------------|----|
| Mean Pre Pressure :  | 2.65       | kN | Min : | 2.59       | kN | Punch NO.; | 34 |
| SD :                 | 1.20       | %  | Max : | 2.73       | kN | Punch NO.; | 53 |
| Mean Main Pressure : | 23.45      | kN | Min : | 21.11      | kN | Punch NO.; | 34 |
| SD :                 | 3.50       | %  | Max : | 24.96      | kN | Punch NO.; | 53 |
| Filling Depth :      | Increase ; | 64 | Times | Decrease ; | 83 | Times      |    |

## PRODUCTION REPORT

### Operation Value

|                               |         |     |                  |          |              |
|-------------------------------|---------|-----|------------------|----------|--------------|
| Disk Speed :                  | 28      | RPM | Capacity :       | 178080   | Tablets/hour |
| Feeder : Status ;             | Auto    |     | Speed ;          | 28       | RPM          |
| Pre Upper Punch Position ;    | 2.99    | mm  |                  |          |              |
| Pre Lower Punch Position ;    | 7.00    | mm  | Pre Thickness ;  | 4.01     | mm           |
| Main Upper Punch Position ;   | 2.99    | mm  |                  |          |              |
| Main Lower Punch Position ;   | 5.60    | mm  | Main Thickness ; | 2.61     | mm           |
| Filling Depth :               | 7.47    | mm  | Current Cam :    | Cam C    |              |
| Main Air pressure :           | 0.801   | MPa |                  | 8.5-14mm |              |
| Oil Lubrication status :      |         |     |                  |          |              |
| Upper Punch Remain Time (S1): | 5       | Min |                  |          |              |
| Lower Punch Remain Time (S2): | 29      | Min |                  |          |              |
| Lower Head Remain Time (S3):  | 0       | Min |                  |          |              |
| Powder Status :               | Disable |     | Dust Collector : | Off      |              |
| Initial Reject :              | Off     |     | Buzzer :         | Off      |              |

### Tightness

|                  |           |      |    |             |    |
|------------------|-----------|------|----|-------------|----|
| Upper Punch :    | Average ; | 0.03 | kN |             |    |
|                  | Max ;     | 0.10 | kN | Max Punch ; | 45 |
| Lower Punch :    | Average ; | 0.10 | kN |             |    |
|                  | Max ;     | 0.15 | kN | Max Punch ; | 24 |
| Ejection Force : | Average ; | 0.03 | kN |             |    |
|                  | Max ;     | 0.06 | kN | Max Punch ; | 12 |

### Tablet Data (N/A)

|                 |                   |         |       |            |         |
|-----------------|-------------------|---------|-------|------------|---------|
| Total Counter : | 950454            | Tablets |       |            |         |
| A.W.C Counter : | 944610            | Tablets |       |            |         |
| HEP :           | 61 (0.0%)         | Tablets | LEP : | 629 (0.1%) | Tablets |
| GOOD :          | 943920<br>(99.9%) | Tablets |       |            |         |