

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	yd98913	Batch NO. :	EWM2512250
Print Interval :	50000 Tablets	Running Time :	11 Hour 40 Min 46 Sec
Total Counter :	2079012	Total Running Time :	1512 Hour 29 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	105	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		70	Min	Supply Time ;	0.1	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.2	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	28.13	kN	No		
HEP :	25.0 %	27.05	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	22.07	kN	Yes	15	Times
Ref :		21.64	kN			
LCP :	2.0 %	21.21	kN	Yes	15	Times
LEP :	25.0 %	16.23	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	15.15	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.91	kN	Min :	2.86	kN	Punch NO.;	23
SD :	0.70	%	Max :	2.95	kN	Punch NO.;	11
Mean Main Pressure :	21.65	kN	Min :	20.54	kN	Punch NO.;	30
SD :	2.50	%	Max :	23.05	kN	Punch NO.;	11
Filling Depth :	Increase ;	17	Times	Decrease ;	27	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	29	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	7.00	mm	Pre Thickness ;	4.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.60	mm	Main Thickness ;	2.61	mm
Filling Depth :	7.83	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.801	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	20	Min			
Lower Punch Remain Time (S2):	34	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.02	kN		
	Max ;	0.09	kN	Max Punch ;	35
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.13	kN	Max Punch ;	23
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.06	kN	Max Punch ;	23

Tablet Data (N/A)

Total Counter :	2079012	Tablets			
A.W.C Counter :	2071214	Tablets			
HEP :	135 (0.0%)	Tablets	LEP :	630 (0.0%)	Tablets
GOOD :	2070449 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	yd98913	Batch NO. :	EWM2512250
Print Interval :	50000 Tablets	Running Time :	11 Hour 40 Min 46 Sec
Total Counter :	2079012	Total Running Time :	1512 Hour 29 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	100	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		70	Min	Supply Time ;	0.1	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.2	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	31.66	kN	No		
HEP :	25.0 %	30.44	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	24.84	kN	Yes 15	Times	
Ref :		24.36	kN			
LCP :	2.0 %	23.87	kN	Yes 15	Times	
LEP :	25.0 %	18.27	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	17.05	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.68	kN	Min :	2.60	kN	Punch NO.;	31
SD :	1.00	%	Max :	2.75	kN	Punch NO.;	27
Mean Main Pressure :	24.49	kN	Min :	22.83	kN	Punch NO.;	31
SD :	3.10	%	Max :	26.08	kN	Punch NO.;	6
Filling Depth :	Increase ;	16	Times	Decrease ;	15	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	28	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	7.00	mm	Pre Thickness ;	4.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.60	mm	Main Thickness ;	2.61	mm
Filling Depth :	7.52	mm	Current Cam :	Cam C	
Main Air pressure :	0.801	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	20	Min			
Lower Punch Remain Time (S2):	34	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.02	kN		
	Max ;	0.09	kN	Max Punch ;	35
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.13	kN	Max Punch ;	10
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.06	kN	Max Punch ;	23

Tablet Data (N/A)

Total Counter :	2079012	Tablets			
A.W.C Counter :	2071214	Tablets			
HEP :	135 (0.0%)	Tablets	LEP :	630 (0.0%)	Tablets
GOOD :	2070449 (100.0%)	Tablets			