

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	cb83530	Batch NO. :	EWM2511950
Print Interval :	50000 Tablets	Running Time :	00 Hour 33 Min 55 Sec
Total Counter :	100062	Total Running Time :	1526 Hour 38 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	100	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		70	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.2	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	12.48	kN	No		
HEP :	22.0 %	11.71	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	9.79	kN	Yes 15	Times	
Ref :		9.60	kN			
LCP :	2.0 %	9.41	kN	Yes 15	Times	
LEP :	22.0 %	7.49	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	6.72	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.83	kN	Min :	2.74	kN	Punch NO.;	48
SD :	1.50	%	Max :	2.97	kN	Punch NO.;	11
Mean Main Pressure :	9.06	kN	Min :	7.08	kN	Punch NO.;	48
SD :	8.30	%	Max :	10.95	kN	Punch NO.;	11
Filling Depth :	Increase ;	161	Times	Decrease ;	158	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	28	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	7.00	mm	Pre Thickness ;	4.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.64	mm	Main Thickness ;	2.65	mm
Filling Depth :	6.84	mm	Current Cam :	Cam C	
Main Air pressure :	0.821	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	34	Min			
Lower Punch Remain Time (S2):	28	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.02	kN		
	Max ;	0.06	kN	Max Punch ;	45
Lower Punch :	Average ;	0.14	kN		
	Max ;	0.15	kN	Max Punch ;	23
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.19	kN	Max Punch ;	52

Tablet Data (N/A)

Total Counter :	100062	Tablets			
A.W.C Counter :	94030	Tablets			
HEP :	240 (0.3%)	Tablets	LEP :	337 (0.4%)	Tablets
GOOD :	93453 (99.4%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	cb83530	Batch NO. :	EWM2511950
Print Interval :	50000 Tablets	Running Time :	00 Hour 33 Min 55 Sec
Total Counter :	100062	Total Running Time :	1526 Hour 38 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	100	%	Manual ;	20	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		70	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.2	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	13.00	kN	No		
HEP :	22.0 %	12.20	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	10.20	kN	Yes 15	Times	
Ref :		10.00	kN			
LCP :	2.0 %	9.80	kN	Yes 15	Times	
LEP :	22.0 %	7.80	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	7.00	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.61	kN	Min :	2.54	kN	Punch NO.;	31
SD :	1.00	%	Max :	2.68	kN	Punch NO.;	12
Mean Main Pressure :	9.92	kN	Min :	8.80	kN	Punch NO.;	31
SD :	5.40	%	Max :	11.03	kN	Punch NO.;	11
Filling Depth :	Increase ;	126	Times	Decrease ;	130	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	28	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	7.00	mm	Pre Thickness ;	4.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.60	mm	Main Thickness ;	2.61	mm
Filling Depth :	7.48	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.821	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	34	Min			
Lower Punch Remain Time (S2):	28	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.02	kN		
	Max ;	0.08	kN	Max Punch ;	42
Lower Punch :	Average ;	0.14	kN		
	Max ;	0.15	kN	Max Punch ;	23
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.19	kN	Max Punch ;	52

Tablet Data (N/A)

Total Counter :	100062	Tablets			
A.W.C Counter :	94030	Tablets			
HEP :	240 (0.3%)	Tablets	LEP :	337 (0.4%)	Tablets
GOOD :	93453 (99.4%)	Tablets			