

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA50MG,STJL1A00
User ID :	ks99394	Batch NO. :	JLM2500450
Print Interval :	50000 Tablets	Running Time :	00 Hour 02 Min 32 Sec
Total Counter :	5810	Total Running Time :	1551 Hour 23 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	35	%	Manual ;	35	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		700000	Tablets			
Air Pressure Low Limit :		0.500	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		70	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.2	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	8.33	kN	No		
HEP :	25.0 %	8.01	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	6.54	kN	Yes 15	Times	
Ref :		6.41	kN			
LCP :	2.0 %	6.28	kN	Yes 15	Times	
LEP :	25.0 %	4.81	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	4.49	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	0.00	kN	Min :	0.00	kN	Punch NO.;	1
		0.00	%	Max :	0.00	kN	Punch NO.;	1
Mean Main Pressure :	SD :	0.00	kN	Min :	0.00	kN	Punch NO.;	1
		0.00	%	Max :	0.00	kN	Punch NO.;	1
Filling Depth :	Increase ;	0	Times	Decrease ;	0	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	5	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.49	mm	Pre Thickness ;	3.50	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.70	mm	Main Thickness ;	1.71	mm
Filling Depth :	5.50	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.800	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	44	Min			
Lower Punch Remain Time (S2):	8	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	On		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	1
Lower Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	1
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	1

Tablet Data (N/A)

Total Counter :	5810	Tablets			
A.W.C Counter :	0	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	0 (0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA50MG,STJL1A00
User ID :	ks99394	Batch NO. :	JLM2500450
Print Interval :	50000 Tablets	Running Time :	00 Hour 02 Min 32 Sec
Total Counter :	5810	Total Running Time :	1551 Hour 23 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	35	%	Manual ;	16	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		700000	Tablets			
Air Pressure Low Limit :		0.500	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		70	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.2	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	5.91	kN	No		
HEP :	24.0 %	5.63	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	4.63	kN	Yes	15	Times
Ref :		4.54	kN			
LCP :	2.0 %	4.45	kN	Yes	15	Times
LEP :	24.0 %	3.45	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	3.18	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	0.00	kN	Min :	0.00	kN	Punch NO.;	1
		0.00	%	Max :	0.00	kN	Punch NO.;	1
Mean Main Pressure :	SD :	0.00	kN	Min :	0.00	kN	Punch NO.;	1
		0.00	%	Max :	0.00	kN	Punch NO.;	1
Filling Depth :	Increase ;	0	Times	Decrease ;	0	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	5	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.49	mm	Pre Thickness ;	3.50	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.79	mm	Main Thickness ;	1.80	mm
Filling Depth :	5.80	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.800	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	44	Min			
Lower Punch Remain Time (S2):	8	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	On		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	1
Lower Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	1
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	1

Tablet Data (N/A)

Total Counter :	5810	Tablets			
A.W.C Counter :	0	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	0 (0%)	Tablets			