

## PRODUCTION REPORT

### Product Information

|                  |               |                      |                       |
|------------------|---------------|----------------------|-----------------------|
| Machine Name :   | VANTIX P720D  | Product Name :       | SERTRA50MG,STJL1A00   |
| User ID :        | sj97904       | Batch NO. :          | JLM2500450            |
| Print Interval : | 50000 Tablets | Running Time :       | 01 Hour 11 Min 43 Sec |
| Total Counter :  | 255962        | Total Running Time : | 1552 Hour 32 Min      |
| Station :        | Station 1     |                      |                       |

### Setting Value

|                                    |             |          |         |                    |              |           |
|------------------------------------|-------------|----------|---------|--------------------|--------------|-----------|
| Feeder :                           | Auto ;      | 30       | %       | Manual ;           | 35           | RPM       |
| Filling Cam :                      |             | Cam B    |         | Cam Range :        | Min :        | 2.50 mm   |
|                                    |             | 4.5-10mm |         |                    | Max :        | 8.00 mm   |
| Target Quantity :                  |             | 700000   | Tablets |                    |              |           |
| Air Pressure Low Limit :           |             | 0.000    | MPa     |                    |              |           |
| Oil Lubrication :                  |             |          |         |                    |              |           |
| Upper Punch Interval Time(S1) ;    |             | 150      | Min     | Supply Time ;      | 0.2          | Sec       |
| Lower Punch Interval Time(S2) ;    |             | 150      | Min     | Supply Time ;      | 0.2          | Sec       |
| Powder Supply Time :               |             | 30.0     | Sec     |                    |              |           |
| Initial Reject Time :              |             | 1        | Tablets |                    |              |           |
| Upper Punch Tightness High Limit : |             | 2.00     | kN      |                    |              |           |
| Lower Punch Tightness High Limit : |             | 4.00     | kN      |                    |              |           |
| Ejecting Force High Limit :        |             | 4.00     | kN      |                    |              |           |
|                                    |             |          |         | Stop Condition ;   |              |           |
| HSP :                              | 30.0 %      | 10.07    | kN      | No                 |              |           |
| HEP :                              | 25.0 %      | 9.69     | kN      | Yes 10             | Rotations 15 | Tablets   |
| HCP :                              | 2.0 %       | 7.90     | kN      | Yes 15             | Times        |           |
| Ref :                              |             | 7.75     | kN      |                    |              |           |
| LCP :                              | 2.0 %       | 7.59     | kN      | Yes 15             | Times        |           |
| LEP :                              | 25.0 %      | 5.81     | kN      | Yes 10             | Rotations 15 | Tablets   |
| LSP :                              | 30.0 %      | 5.42     | kN      | No                 |              |           |
| SD limit :                         | 35.0 %      |          |         | Yes                |              |           |
| Pre HSP                            |             | 30.00    | kN      | Yes                |              |           |
| Mean Calculation range :           | 2 Rotations |          |         | Calculation Pass : | 1            | Rotations |
| Empty Punch No. :                  | None        |          |         |                    |              |           |

### Pressure Data

|                      |               |       |            |      |       |            |    |
|----------------------|---------------|-------|------------|------|-------|------------|----|
| Mean Pre Pressure :  | 2.60          | kN    | Min :      | 2.55 | kN    | Punch NO.; | 61 |
| SD :                 | 0.60          | %     | Max :      | 2.63 | kN    | Punch NO.; | 42 |
| Mean Main Pressure : | 7.83          | kN    | Min :      | 7.37 | kN    | Punch NO.; | 63 |
| SD :                 | 3.10          | %     | Max :      | 8.61 | kN    | Punch NO.; | 35 |
| Filling Depth :      | Increase ; 66 | Times | Decrease ; | 46   | Times |            |    |

## PRODUCTION REPORT

### Operation Value

|                               |         |     |                  |          |              |
|-------------------------------|---------|-----|------------------|----------|--------------|
| Disk Speed :                  | 30      | RPM | Capacity :       | 277200   | Tablets/hour |
| Feeder : Status ;             | Auto    |     | Speed ;          | 9        | RPM          |
| Pre Upper Punch Position ;    | 2.99    | mm  |                  |          |              |
| Pre Lower Punch Position ;    | 6.49    | mm  | Pre Thickness ;  | 3.50     | mm           |
| Main Upper Punch Position ;   | 2.99    | mm  |                  |          |              |
| Main Lower Punch Position ;   | 4.67    | mm  | Main Thickness ; | 1.68     | mm           |
| Filling Depth :               | 6.02    | mm  | Current Cam :    | Cam B    |              |
| Main Air pressure :           | 0.808   | MPa |                  | 4.5-10mm |              |
| Oil Lubrication status :      |         |     |                  |          |              |
| Upper Punch Remain Time (S1): | 109     | Min |                  |          |              |
| Lower Punch Remain Time (S2): | 83      | Min |                  |          |              |
| Lower Head Remain Time (S3):  | 0       | Min |                  |          |              |
| Powder Status :               | Disable |     | Dust Collector : | Off      |              |
| Initial Reject :              | Off     |     | Buzzer :         | Off      |              |

### Tightness

|                  |           |      |    |             |    |
|------------------|-----------|------|----|-------------|----|
| Upper Punch :    | Average ; | 0.90 | kN |             |    |
|                  | Max ;     | 1.10 | kN | Max Punch ; | 17 |
| Lower Punch :    | Average ; | 0.08 | kN |             |    |
|                  | Max ;     | 0.09 | kN | Max Punch ; | 17 |
| Ejection Force : | Average ; | 0.04 | kN |             |    |
|                  | Max ;     | 0.08 | kN | Max Punch ; | 74 |

### Tablet Data (N/A)

|                 |                   |         |       |            |         |
|-----------------|-------------------|---------|-------|------------|---------|
| Total Counter : | 255962            | Tablets |       |            |         |
| A.W.C Counter : | 224247            | Tablets |       |            |         |
| HEP :           | 1027 (0.5%)       | Tablets | LEP : | 173 (0.1%) | Tablets |
| GOOD :          | 223047<br>(99.5%) | Tablets |       |            |         |

## PRODUCTION REPORT

### Product Information

|                  |               |                      |                       |
|------------------|---------------|----------------------|-----------------------|
| Machine Name :   | VANTIX P720D  | Product Name :       | SERTRA50MG,STJL1A00   |
| User ID :        | sj97904       | Batch NO. :          | JLM2500450            |
| Print Interval : | 50000 Tablets | Running Time :       | 01 Hour 11 Min 43 Sec |
| Total Counter :  | 255962        | Total Running Time : | 1552 Hour 32 Min      |
| Station :        | Station 2     |                      |                       |

### Setting Value

|                                    |        |           |         |                    |              |           |
|------------------------------------|--------|-----------|---------|--------------------|--------------|-----------|
| Feeder :                           | Auto ; | 30        | %       | Manual ;           | 16           | RPM       |
| Filling Cam :                      |        | Cam B     |         | Cam Range :        | Min :        | 2.50 mm   |
|                                    |        | 4.5-10mm  |         |                    | Max :        | 8.00 mm   |
| Target Quantity :                  |        | 700000    | Tablets |                    |              |           |
| Air Pressure Low Limit :           |        | 0.000     | MPa     |                    |              |           |
| Oil Lubrication :                  |        |           |         |                    |              |           |
| Upper Punch Interval Time(S1) ;    |        | 150       | Min     | Supply Time ;      | 0.2          | Sec       |
| Lower Punch Interval Time(S2) ;    |        | 150       | Min     | Supply Time ;      | 0.2          | Sec       |
| Powder Supply Time :               |        | 30.0      | Sec     |                    |              |           |
| Initial Reject Time :              |        | 1         | Tablets |                    |              |           |
| Upper Punch Tightness High Limit : |        | 2.00      | kN      |                    |              |           |
| Lower Punch Tightness High Limit : |        | 4.00      | kN      |                    |              |           |
| Ejecting Force High Limit :        |        | 4.00      | kN      |                    |              |           |
|                                    |        |           |         | Stop Condition ;   |              |           |
| HSP :                              | 30.0 % | 9.77      | kN      | No                 |              |           |
| HEP :                              | 24.0 % | 9.32      | kN      | Yes 10             | Rotations 15 | Tablets   |
| HCP :                              | 2.0 %  | 7.67      | kN      | Yes 15             | Times        |           |
| Ref :                              |        | 7.52      | kN      |                    |              |           |
| LCP :                              | 2.0 %  | 7.36      | kN      | Yes 15             | Times        |           |
| LEP :                              | 24.0 % | 5.71      | kN      | Yes 10             | Rotations 15 | Tablets   |
| LSP :                              | 30.0 % | 5.26      | kN      | No                 |              |           |
| SD limit :                         | 35.0 % |           |         | Yes                |              |           |
| Pre HSP                            |        | 30.00     | kN      | Yes                |              |           |
| Mean Calculation range :           | 2      | Rotations |         | Calculation Pass : | 1            | Rotations |
| Empty Punch No. :                  | N      |           |         |                    |              |           |

### Pressure Data

|                      |            |     |       |            |     |            |    |
|----------------------|------------|-----|-------|------------|-----|------------|----|
| Mean Pre Pressure :  | 2.39       | kN  | Min : | 2.36       | kN  | Punch NO.; | 23 |
| SD :                 | 0.70       | %   | Max : | 2.43       | kN  | Punch NO.; | 35 |
| Mean Main Pressure : | 7.51       | kN  | Min : | 6.79       | kN  | Punch NO.; | 16 |
| SD :                 | 4.70       | %   | Max : | 9.17       | kN  | Punch NO.; | 35 |
| Filling Depth :      | Increase ; | 103 | Times | Decrease ; | 100 | Times      |    |

## PRODUCTION REPORT

### Operation Value

|                               |         |     |                  |          |              |
|-------------------------------|---------|-----|------------------|----------|--------------|
| Disk Speed :                  | 30      | RPM | Capacity :       | 277200   | Tablets/hour |
| Feeder : Status ;             | Auto    |     | Speed ;          | 9        | RPM          |
| Pre Upper Punch Position ;    | 2.99    | mm  |                  |          |              |
| Pre Lower Punch Position ;    | 6.49    | mm  | Pre Thickness ;  | 3.50     | mm           |
| Main Upper Punch Position ;   | 2.99    | mm  |                  |          |              |
| Main Lower Punch Position ;   | 4.75    | mm  | Main Thickness ; | 1.76     | mm           |
| Filling Depth :               | 6.16    | mm  | Current Cam :    | Cam B    |              |
| Main Air pressure :           | 0.808   | MPa |                  | 4.5-10mm |              |
| Oil Lubrication status :      |         |     |                  |          |              |
| Upper Punch Remain Time (S1): | 109     | Min |                  |          |              |
| Lower Punch Remain Time (S2): | 83      | Min |                  |          |              |
| Lower Head Remain Time (S3):  | 0       | Min |                  |          |              |
| Powder Status :               | Disable |     | Dust Collector : | Off      |              |
| Initial Reject :              | Off     |     | Buzzer :         | Off      |              |

### Tightness

|                  |           |      |    |             |    |
|------------------|-----------|------|----|-------------|----|
| Upper Punch :    | Average ; | 0.86 | kN |             |    |
|                  | Max ;     | 1.16 | kN | Max Punch ; | 2  |
| Lower Punch :    | Average ; | 0.08 | kN |             |    |
|                  | Max ;     | 0.09 | kN | Max Punch ; | 17 |
| Ejection Force : | Average ; | 0.04 | kN |             |    |
|                  | Max ;     | 0.08 | kN | Max Punch ; | 74 |

### Tablet Data (N/A)

|                 |                   |         |       |            |         |
|-----------------|-------------------|---------|-------|------------|---------|
| Total Counter : | 255962            | Tablets |       |            |         |
| A.W.C Counter : | 224247            | Tablets |       |            |         |
| HEP :           | 1027 (0.5%)       | Tablets | LEP : | 173 (0.1%) | Tablets |
| GOOD :          | 223047<br>(99.5%) | Tablets |       |            |         |