

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA50MG,STJL1A0 0
User ID :	pb97604	Batch NO. :	JLM2500550
Print Interval :	50000 Tablets	Running Time :	00 Hour 21 Min 45 Sec
Total Counter :	50026	Total Running Time :	1554 Hour 36 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	23	%	Manual ;	35	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		700000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		150	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		150	Min	Supply Time ;	0.2	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	9.83	kN	No		
HEP :	25.0 %	9.45	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	7.71	kN	Yes 15	Times	
Ref :		7.56	kN			
LCP :	2.0 %	7.41	kN	Yes 15	Times	
LEP :	25.0 %	5.67	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	5.29	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.59	kN	Min :	2.56	kN	Punch NO.;	13
SD :	0.30	%	Max :	2.60	kN	Punch NO.;	3
Mean Main Pressure :	7.56	kN	Min :	7.28	kN	Punch NO.;	16
SD :	1.70	%	Max :	7.84	kN	Punch NO.;	31
Filling Depth :	Increase ; 116	Times	Decrease ;	113	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	138600	Tablets/hour
Feeder : Status ;	Auto		Speed ;	3	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.49	mm	Pre Thickness ;	3.50	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.70	mm	Main Thickness ;	1.71	mm
Filling Depth :	5.94	mm	Current Cam :	Cam B	
Main Air pressure :	0.712	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	25	Min			
Lower Punch Remain Time (S2):	149	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.17	kN		
	Max ;	0.19	kN	Max Punch ;	25
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.09	kN	Max Punch ;	17
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.06	kN	Max Punch ;	17

Tablet Data (N/A)

Total Counter :	50026	Tablets			
A.W.C Counter :	46699	Tablets			
HEP :	25 (0.1%)	Tablets	LEP :	70 (0.1%)	Tablets
GOOD :	46604 (99.8%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA50MG,STJL1A00
User ID :	pb97604	Batch NO. :	JLM2500550
Print Interval :	50000 Tablets	Running Time :	00 Hour 21 Min 45 Sec
Total Counter :	50026	Total Running Time :	1554 Hour 36 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	23	%	Manual ;	16	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		700000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		150	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		150	Min	Supply Time ;	0.2	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	9.06	kN	No		
HEP :	25.0 %	8.71	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	7.11	kN	Yes 15	Times	
Ref :		6.97	kN			
LCP :	2.0 %	6.83	kN	Yes 15	Times	
LEP :	25.0 %	5.23	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	4.88	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.24	kN	Min :	2.22	kN	Punch NO.;	16
SD :	0.50	%	Max :	2.28	kN	Punch NO.;	43
Mean Main Pressure :	6.93	kN	Min :	6.52	kN	Punch NO.;	18
SD :	3.70	%	Max :	8.38	kN	Punch NO.;	76
Filling Depth :	Increase ;	179	Times	Decrease ;	148	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	138600	Tablets/hour
Feeder : Status ;	Auto		Speed ;	3	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.79	mm	Pre Thickness ;	3.80	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.77	mm	Main Thickness ;	1.78	mm
Filling Depth :	5.98	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.712	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	25	Min			
Lower Punch Remain Time (S2):	149	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.17	kN		
	Max ;	0.19	kN	Max Punch ;	25
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.09	kN	Max Punch ;	17
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.06	kN	Max Punch ;	17

Tablet Data (N/A)

Total Counter :	50026	Tablets			
A.W.C Counter :	46699	Tablets			
HEP :	25 (0.1%)	Tablets	LEP :	70 (0.1%)	Tablets
GOOD :	46604 (99.8%)	Tablets			