

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA50MG STJL1A00
User ID :	sj97904	Batch NO. :	JLM2500650
Print Interval :	50000 Tablets	Running Time :	00 Hour 46 Min 38 Sec
Total Counter :	150078	Total Running Time :	1558 Hour 3 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	24	%	Manual ;	35	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		700000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		150	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		150	Min	Supply Time ;	0.2	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	11.71	kN	No		
HEP :	25.0 %	11.26	kN	Yes	10 Rotations	15 Tablets
HCP :	2.0 %	9.19	kN	Yes	15 Times	
Ref :		9.01	kN			
LCP :	2.0 %	8.83	kN	Yes	15 Times	
LEP :	25.0 %	6.76	kN	Yes	10 Rotations	15 Tablets
LSP :	30.0 %	6.31	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.66	kN	Min :	2.63	kN	Punch NO.;	13
SD :	0.40	%	Max :	2.70	kN	Punch NO.;	50
Mean Main Pressure :	9.10	kN	Min :	8.45	kN	Punch NO.;	16
SD :	2.80	%	Max :	9.60	kN	Punch NO.;	52
Filling Depth :	Increase ;	225	Times	Decrease ;	252	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	30	RPM	Capacity :	277200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	7	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.40	mm	Pre Thickness ;	3.41	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.58	mm	Main Thickness ;	1.59	mm
Filling Depth :	6.15	mm	Current Cam :	Cam B	
Main Air pressure :	0.810	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	133	Min			
Lower Punch Remain Time (S2):	107	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.17	kN		
	Max ;	0.23	kN	Max Punch ;	3
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.11	kN	Max Punch ;	3
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.06	kN	Max Punch ;	76

Tablet Data (N/A)

Total Counter :	150078	Tablets			
A.W.C Counter :	137397	Tablets			
HEP :	420 (0.3%)	Tablets	LEP :	312 (0.2%)	Tablets
GOOD :	136665 (99.5%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA50MG STJL1A00
User ID :	sj97904	Batch NO. :	JLM2500650
Print Interval :	50000 Tablets	Running Time :	00 Hour 46 Min 38 Sec
Total Counter :	150078	Total Running Time :	1558 Hour 3 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	26	%	Manual ;	16	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		700000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		150	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		150	Min	Supply Time ;	0.2	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	11.12	kN	No		
HEP :	25.0 %	10.70	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	8.73	kN	Yes	15	Times
Ref :		8.56	kN			
LCP :	2.0 %	8.39	kN	Yes	15	Times
LEP :	25.0 %	6.42	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	5.99	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.32	kN	Min :	2.29	kN	Punch NO.;	46
SD :	0.50	%	Max :	2.36	kN	Punch NO.;	3
Mean Main Pressure :	8.24	kN	Min :	7.51	kN	Punch NO.;	56
SD :	4.10	%	Max :	9.25	kN	Punch NO.;	2
Filling Depth :	Increase ;	253	Times	Decrease ;	231	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	30	RPM	Capacity :	277200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	8	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.75	mm	Pre Thickness ;	3.76	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.67	mm	Main Thickness ;	1.68	mm
Filling Depth :	6.21	mm	Current Cam :	Cam B	
Main Air pressure :	0.810	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	133	Min			
Lower Punch Remain Time (S2):	107	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.17	kN		
	Max ;	0.23	kN	Max Punch ;	3
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.11	kN	Max Punch ;	3
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.07	kN	Max Punch ;	24

Tablet Data (N/A)

Total Counter :	150078	Tablets			
A.W.C Counter :	137397	Tablets			
HEP :	420 (0.3%)	Tablets	LEP :	312 (0.2%)	Tablets
GOOD :	136665 (99.5%)	Tablets			