

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA100MG STJL1B00
User ID :	rp98927	Batch NO. :	JLM2500410
Print Interval :	50000 Tablets	Running Time :	01 Hour 09 Min 46 Sec
Total Counter :	225504	Total Running Time :	1561 Hour 24 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	44	%	Manual ;	33	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		650000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		25	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	14.86	kN	No		
HEP :	25.0 %	14.29	kN	Yes	10 Rotations	15 Tablets
HCP :	2.0 %	11.66	kN	Yes	15 Times	
Ref :		11.43	kN			
LCP :	2.0 %	11.20	kN	Yes	15 Times	
LEP :	25.0 %	8.57	kN	Yes	10 Rotations	15 Tablets
LSP :	30.0 %	8.00	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.92	kN	Min :	2.86	kN	Punch NO.;	16
SD :	0.50	%	Max :	2.95	kN	Punch NO.;	36
Mean Main Pressure :	11.38	kN	Min :	10.66	kN	Punch NO.;	16
SD :	2.40	%	Max :	12.57	kN	Punch NO.;	36
Filling Depth :	Increase ;	25	Times	Decrease ;	31	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	30	RPM	Capacity :	277200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	13	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	7.00	mm	Pre Thickness ;	4.01	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.97	mm	Main Thickness ;	1.97	mm
Filling Depth :	7.55	mm	Current Cam :	Cam B	
Main Air pressure :	0.805	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	11	Min			
Lower Punch Remain Time (S2):	16	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.78	kN		
	Max ;	1.15	kN	Max Punch ;	73
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.11	kN	Max Punch ;	49
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	225504	Tablets			
A.W.C Counter :	209784	Tablets			
HEP :	9 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	209775 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA100MG STJL1B00
User ID :	rp98927	Batch NO. :	JLM2500410
Print Interval :	50000 Tablets	Running Time :	01 Hour 09 Min 46 Sec
Total Counter :	225504	Total Running Time :	1561 Hour 24 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	61	%	Manual ;	16	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		650000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		25	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	12.25	kN	No		
HEP :	25.0 %	11.78	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	9.61	kN	Yes	15	Times
Ref :		9.42	kN			
LCP :	2.0 %	9.24	kN	Yes	15	Times
LEP :	25.0 %	7.07	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	6.60	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.74	kN	Min :	2.68	kN	Punch NO.;	16
SD :	1.00	%	Max :	2.82	kN	Punch NO.;	35
Mean Main Pressure :	9.34	kN	Min :	8.52	kN	Punch NO.;	16
SD :	5.30	%	Max :	10.92	kN	Punch NO.;	36
Filling Depth :	Increase ;	10	Times	Decrease ;	13	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	30	RPM	Capacity :	277200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	18	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	7.00	mm	Pre Thickness ;	4.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.18	mm	Main Thickness ;	2.19	mm
Filling Depth :	7.79	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.805	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	11	Min			
Lower Punch Remain Time (S2):	16	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.78	kN		
	Max ;	1.15	kN	Max Punch ;	73
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.11	kN	Max Punch ;	64
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	225504	Tablets			
A.W.C Counter :	209784	Tablets			
HEP :	9 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	209775 (100.0%)	Tablets			