

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA100MG STJL1B00
User ID :	pb97604	Batch NO. :	JLM2500510
Print Interval :	50000 Tablets	Running Time :	01 Hour 58 Min 43 Sec
Total Counter :	450294	Total Running Time :	1565 Hour 3 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	51	%	Manual ;	33	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		650000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		25	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	15.24	kN	No		
HEP :	25.0 %	14.65	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	11.96	kN	Yes 15	Times	
Ref :		11.72	kN			
LCP :	2.0 %	11.49	kN	Yes 15	Times	
LEP :	25.0 %	8.79	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	8.21	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.93	kN	Min :	2.91	kN	Punch NO.;	11
SD :	0.40	%	Max :	2.97	kN	Punch NO.;	36
Mean Main Pressure :	11.77	kN	Min :	11.25	kN	Punch NO.;	23
SD :	2.20	%	Max :	12.69	kN	Punch NO.;	36
Filling Depth :	Increase ; 79	Times	Decrease ;	101	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	231000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	13	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	7.00	mm	Pre Thickness ;	4.01	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.02	mm	Main Thickness ;	2.02	mm
Filling Depth :	7.09	mm	Current Cam :	Cam B	
Main Air pressure :	0.798	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	25	Min			
Lower Punch Remain Time (S2):	5	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.22	kN		
	Max ;	0.29	kN	Max Punch ;	38
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.11	kN	Max Punch ;	47
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	450294	Tablets			
A.W.C Counter :	443928	Tablets			
HEP :	69 (0.0%)	Tablets	LEP :	1 (0.0%)	Tablets
GOOD :	443858 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA100MG STJL1B00
User ID :	pb97604	Batch NO. :	JLM2500510
Print Interval :	50000 Tablets	Running Time :	01 Hour 58 Min 43 Sec
Total Counter :	450294	Total Running Time :	1565 Hour 3 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	54	%	Manual ;	16	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		650000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		25	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	12.62	kN	No		
HEP :	25.0 %	12.13	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	9.90	kN	Yes 15	Times	
Ref :		9.71	kN			
LCP :	2.0 %	9.51	kN	Yes 15	Times	
LEP :	25.0 %	7.28	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	6.79	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.71	kN	Min :	2.68	kN	Punch NO.;	9
SD :	0.70	%	Max :	2.77	kN	Punch NO.;	35
Mean Main Pressure :	9.83	kN	Min :	9.24	kN	Punch NO.;	22
SD :	4.00	%	Max :	11.47	kN	Punch NO.;	36
Filling Depth :	Increase ;	56	Times	Decrease ;	55	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	231000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	7.00	mm	Pre Thickness ;	4.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.18	mm	Main Thickness ;	2.19	mm
Filling Depth :	7.67	mm	Current Cam :	Cam B	
Main Air pressure :	0.798	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	25	Min			
Lower Punch Remain Time (S2):	5	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.22	kN		
	Max ;	0.29	kN	Max Punch ;	76
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.11	kN	Max Punch ;	47
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	450294	Tablets			
A.W.C Counter :	443928	Tablets			
HEP :	69 (0.0%)	Tablets	LEP :	1 (0.0%)	Tablets
GOOD :	443858 (100.0%)	Tablets			