

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA100MG STJL1B00
User ID :	sj97904	Batch NO. :	JLM2500610
Print Interval :	50000 Tablets	Running Time :	00 Hour 59 Min 05 Sec
Total Counter :	200178	Total Running Time :	1566 Hour 48 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	52	%	Manual ;	33	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		650000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		25	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	15.09	kN	No		
HEP :	25.0 %	14.51	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	11.84	kN	Yes 15	Times	
Ref :		11.61	kN			
LCP :	2.0 %	11.37	kN	Yes 15	Times	
LEP :	25.0 %	8.70	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	8.12	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.96	kN	Min :	2.92	kN	Punch NO.;	4
SD :	0.40	%	Max :	3.00	kN	Punch NO.;	35
Mean Main Pressure :	11.64	kN	Min :	10.88	kN	Punch NO.;	4
SD :	2.60	%	Max :	12.95	kN	Punch NO.;	36
Filling Depth :	Increase ;	103	Times	Decrease ;	124	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	30	RPM	Capacity :	277200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	16	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	7.00	mm	Pre Thickness ;	4.01	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.00	mm	Main Thickness ;	2.00	mm
Filling Depth :	7.29	mm	Current Cam :	Cam B	
Main Air pressure :	0.798	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	22	Min			
Lower Punch Remain Time (S2):	3	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.43	kN		
	Max ;	0.51	kN	Max Punch ;	77
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.12	kN	Max Punch ;	16
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	200178	Tablets			
A.W.C Counter :	191356	Tablets			
HEP :	293 (0.2%)	Tablets	LEP :	350 (0.2%)	Tablets
GOOD :	190713 (99.7%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA100MG STJL1B00
User ID :	sj97904	Batch NO. :	JLM2500610
Print Interval :	50000 Tablets	Running Time :	00 Hour 59 Min 05 Sec
Total Counter :	200178	Total Running Time :	1566 Hour 48 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	50	%	Manual ;	16	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		650000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		25	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	13.50	kN	No		
HEP :	25.0 %	12.98	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	10.59	kN	Yes	15	Times
Ref :		10.39	kN			
LCP :	2.0 %	10.18	kN	Yes	15	Times
LEP :	25.0 %	7.79	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	7.27	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.74	kN	Min :	2.69	kN	Punch NO.;	4
SD :	0.70	%	Max :	2.82	kN	Punch NO.;	76
Mean Main Pressure :	10.39	kN	Min :	9.48	kN	Punch NO.;	16
SD :	4.90	%	Max :	12.77	kN	Punch NO.;	36
Filling Depth :	Increase ;	79	Times	Decrease ;	70	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	30	RPM	Capacity :	277200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	15	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	7.00	mm	Pre Thickness ;	4.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.13	mm	Main Thickness ;	2.14	mm
Filling Depth :	7.82	mm	Current Cam :	Cam B	
Main Air pressure :	0.798	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	22	Min			
Lower Punch Remain Time (S2):	3	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.43	kN		
	Max ;	0.53	kN	Max Punch ;	18
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.12	kN	Max Punch ;	16
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	200178	Tablets			
A.W.C Counter :	191356	Tablets			
HEP :	293 (0.2%)	Tablets	LEP :	350 (0.2%)	Tablets
GOOD :	190713 (99.7%)	Tablets			