

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA100MG STJL1B00
User ID :	sj97904	Batch NO. :	JLM2500610
Print Interval :	50000 Tablets	Running Time :	01 Hour 09 Min 55 Sec
Total Counter :	250196	Total Running Time :	1566 Hour 59 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	58	%	Manual ;	33	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		650000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		25	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	15.09	kN	No		
HEP :	25.0 %	14.51	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	11.84	kN	Yes 15	Times	
Ref :		11.61	kN			
LCP :	2.0 %	11.38	kN	Yes 15	Times	
LEP :	25.0 %	8.71	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	8.13	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.97	kN	Min :	2.93	kN	Punch NO.;	39
SD :	0.40	%	Max :	3.00	kN	Punch NO.;	35
Mean Main Pressure :	11.47	kN	Min :	10.93	kN	Punch NO.;	50
SD :	2.30	%	Max :	12.29	kN	Punch NO.;	36
Filling Depth :	Increase ;	109	Times	Decrease ;	126	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	30	RPM	Capacity :	277200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	17	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	7.00	mm	Pre Thickness ;	4.01	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.00	mm	Main Thickness ;	2.00	mm
Filling Depth :	7.76	mm	Current Cam :	Cam B	
Main Air pressure :	0.797	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	11	Min			
Lower Punch Remain Time (S2):	12	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.43	kN		
	Max ;	0.53	kN	Max Punch ;	18
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.12	kN	Max Punch ;	47
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	250196	Tablets			
A.W.C Counter :	240909	Tablets			
HEP :	295 (0.1%)	Tablets	LEP :	489 (0.2%)	Tablets
GOOD :	240125 (99.7%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA100MG STJL1B00
User ID :	sj97904	Batch NO. :	JLM2500610
Print Interval :	50000 Tablets	Running Time :	01 Hour 09 Min 55 Sec
Total Counter :	250196	Total Running Time :	1566 Hour 59 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	52	%	Manual ;	16	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		650000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		25	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	13.94	kN	No		
HEP :	25.0 %	13.41	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	10.94	kN	Yes 15	Times	
Ref :		10.73	kN			
LCP :	2.0 %	10.51	kN	Yes 15	Times	
LEP :	25.0 %	8.04	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	7.51	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.74	kN	Min :	2.70	kN	Punch NO.;	17
SD :	0.80	%	Max :	2.82	kN	Punch NO.;	36
Mean Main Pressure :	10.64	kN	Min :	9.86	kN	Punch NO.;	16
SD :	4.00	%	Max :	12.57	kN	Punch NO.;	36
Filling Depth :	Increase ;	91	Times	Decrease ;	74	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	30	RPM	Capacity :	277200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	16	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	7.00	mm	Pre Thickness ;	4.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.11	mm	Main Thickness ;	2.12	mm
Filling Depth :	7.79	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.797	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	11	Min			
Lower Punch Remain Time (S2):	12	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.43	kN		
	Max ;	0.53	kN	Max Punch ;	18
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.12	kN	Max Punch ;	47
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	250196	Tablets			
A.W.C Counter :	240909	Tablets			
HEP :	295 (0.1%)	Tablets	LEP :	489 (0.2%)	Tablets
GOOD :	240125 (99.7%)	Tablets			