

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU 400 MG STIR1B00
User ID :	pb97604	Batch NO. :	IRM2507840
Print Interval :	50000 Tablets	Running Time :	01 Hour 50 Min 11 Sec
Total Counter :	206172	Total Running Time :	1570 Hour 27 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	139	%	Manual ;	33	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
Target Quantity :		8.5-14mm			Max :	12.00 mm
Air Pressure Low Limit :		1000000	Tablets			
Oil Lubrication :		0.400	MPa			
Upper Punch Interval Time(S1) ;		25	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	18.73	kN	No		
HEP :	20.0 %	17.29	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	14.70	kN	Yes 15	Times	
Ref :		14.41	kN			
LCP :	2.0 %	14.12	kN	Yes 15	Times	
LEP :	20.0 %	11.53	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	10.09	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	1.67	kN	Min :	1.49	kN	Punch NO.;	31
		4.70	%	Max :	1.80	kN	Punch NO.;	34
Mean Main Pressure :		14.46	kN	Min :	14.40	kN	Punch NO.;	16
	SD :	0.20	%	Max :	14.58	kN	Punch NO.;	24
Filling Depth :	Increase ;	0	Times	Decrease ;	0	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	114480	Tablets/hour
Feeder : Status ;	Auto		Speed ;	25	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.20	mm	Pre Thickness ;	2.21	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.42	mm	Main Thickness ;	1.42	mm
Filling Depth :	7.26	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.711	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	13	Min			
Lower Punch Remain Time (S2):	14	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.38	kN		
	Max ;	0.42	kN	Max Punch ;	53
Lower Punch :	Average ;	0.03	kN		
	Max ;	0.03	kN	Max Punch ;	1
Ejection Force :	Average ;	0.16	kN		
	Max ;	0.20	kN	Max Punch ;	9

Tablet Data (N/A)

Total Counter :	206172	Tablets			
A.W.C Counter :	197844	Tablets			
HEP :	130 (0.1%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	197714 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU 400 MG STIR1B00
User ID :	pb97604	Batch NO. :	IRM2507840
Print Interval :	50000 Tablets	Running Time :	01 Hour 50 Min 11 Sec
Total Counter :	206172	Total Running Time :	1570 Hour 27 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	154	%	Manual ;	16	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
Target Quantity :		8.5-14mm			Max :	12.00 mm
Air Pressure Low Limit :		1000000	Tablets			
Oil Lubrication :		0.400	MPa			
Upper Punch Interval Time(S1) ;		25	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	18.74	kN	No		
HEP :	20.0 %	17.30	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	14.70	kN	Yes	15	Times
Ref :		14.42	kN			
LCP :	2.0 %	14.13	kN	Yes	15	Times
LEP :	20.0 %	11.53	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	10.09	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	1.87	kN	Min :	1.74	kN	Punch NO.;	33
		3.90	%	Max :	2.04	kN	Punch NO.;	7
Mean Main Pressure :		14.39	kN	Min :	14.34	kN	Punch NO.;	4
	SD :	0.20	%	Max :	14.46	kN	Punch NO.;	1
Filling Depth :	Increase ;	0	Times	Decrease ;	0	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	114480	Tablets/hour
Feeder : Status ;	Auto		Speed ;	28	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.20	mm	Pre Thickness ;	2.21	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.45	mm	Main Thickness ;	1.45	mm
Filling Depth :	7.66	mm	Current Cam :	Cam C	
Main Air pressure :	0.711	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	13	Min			
Lower Punch Remain Time (S2):	14	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.38	kN		
	Max ;	0.42	kN	Max Punch ;	53
Lower Punch :	Average ;	0.03	kN		
	Max ;	0.03	kN	Max Punch ;	1
Ejection Force :	Average ;	0.16	kN		
	Max ;	0.20	kN	Max Punch ;	9

Tablet Data (N/A)

Total Counter :	206172	Tablets			
A.W.C Counter :	197844	Tablets			
HEP :	130 (0.1%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	197714 (99.9%)	Tablets			