

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU 400 MG STIR1B00
User ID :	pb97604	Batch NO. :	IRM2507840
Print Interval :	50000 Tablets	Running Time :	05 Hour 24 Min 13 Sec
Total Counter :	606304	Total Running Time :	1574 Hour 1 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	186	%	Manual ;	33	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
Target Quantity :		8.5-14mm			Max :	12.00 mm
Air Pressure Low Limit :		1000000	Tablets			
Oil Lubrication :		0.400	MPa			
Upper Punch Interval Time(S1) ;		25	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	18.75	kN	No		
HEP :	20.0 %	17.31	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	14.71	kN	Yes	15	Times
Ref :		14.43	kN			
LCP :	2.0 %	14.14	kN	Yes	15	Times
LEP :	20.0 %	11.54	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	10.10	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	1.78	kN	Min :	1.60	kN	Punch NO.;	29
		4.50	%	Max :	2.01	kN	Punch NO.;	7
Mean Main Pressure :		14.43	kN	Min :	14.39	kN	Punch NO.;	43
	SD :	0.20	%	Max :	14.55	kN	Punch NO.;	24
Filling Depth :	Increase ;	0	Times	Decrease ;	0	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	16	RPM	Capacity :	101760	Tablets/hour
Feeder : Status ;	Auto		Speed ;	30	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.20	mm	Pre Thickness ;	2.21	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.42	mm	Main Thickness ;	1.42	mm
Filling Depth :	7.61	mm	Current Cam :	Cam C	
Main Air pressure :	0.732	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	25	Min			
Lower Punch Remain Time (S2):	11	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.41	kN		
	Max ;	0.45	kN	Max Punch ;	53
Lower Punch :	Average ;	0.03	kN		
	Max ;	0.03	kN	Max Punch ;	38
Ejection Force :	Average ;	0.17	kN		
	Max ;	0.21	kN	Max Punch ;	18

Tablet Data (N/A)

Total Counter :	606304	Tablets			
A.W.C Counter :	597942	Tablets			
HEP :	130 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	597812 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU 400 MG STIR1B00
User ID :	pb97604	Batch NO. :	IRM2507840
Print Interval :	50000 Tablets	Running Time :	05 Hour 24 Min 13 Sec
Total Counter :	606304	Total Running Time :	1574 Hour 1 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	176	%	Manual ;	16	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		1000000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		25	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	18.70	kN	No		
HEP :	20.0 %	17.26	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	14.67	kN	Yes 15	Times	
Ref :		14.38	kN			
LCP :	2.0 %	14.10	kN	Yes 15	Times	
LEP :	20.0 %	11.51	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	10.07	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.95	kN	Min :	1.77	kN	Punch NO.;	43
SD :	5.10	%	Max :	2.22	kN	Punch NO.;	48
Mean Main Pressure :	14.40	kN	Min :	14.34	kN	Punch NO.;	18
SD :	0.10	%	Max :	14.46	kN	Punch NO.;	12
Filling Depth :	Increase ; 0	Times	Decrease ; 0	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	16	RPM	Capacity :	101760	Tablets/hour
Feeder : Status ;	Auto		Speed ;	28	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.20	mm	Pre Thickness ;	2.21	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.45	mm	Main Thickness ;	1.45	mm
Filling Depth :	7.69	mm	Current Cam :	Cam C	
Main Air pressure :	0.732	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	25	Min			
Lower Punch Remain Time (S2):	11	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.41	kN		
	Max ;	0.45	kN	Max Punch ;	53
Lower Punch :	Average ;	0.03	kN		
	Max ;	0.04	kN	Max Punch ;	50
Ejection Force :	Average ;	0.17	kN		
	Max ;	0.22	kN	Max Punch ;	18

Tablet Data (N/A)

Total Counter :	606304	Tablets			
A.W.C Counter :	597942	Tablets			
HEP :	130 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	597812 (100.0%)	Tablets			