

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU 400 MG STIR1B00
User ID :	rp98927	Batch NO. :	IRM2507840
Print Interval :	50000 Tablets	Running Time :	08 Hour 40 Min 01 Sec
Total Counter :	936688	Total Running Time :	1577 Hour 16 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	186	%	Manual ;	33	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		1000000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		25	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	18.75	kN	No		
HEP :	20.0 %	17.31	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	14.71	kN	Yes 15	Times	
Ref :		14.43	kN			
LCP :	2.0 %	14.14	kN	Yes 15	Times	
LEP :	20.0 %	11.54	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	10.10	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.52	kN	Min :	1.31	kN	Punch NO.;	35
SD :	6.70	%	Max :	1.79	kN	Punch NO.;	32
Mean Main Pressure :	13.39	kN	Min :	11.91	kN	Punch NO.;	4
SD :	5.80	%	Max :	15.97	kN	Punch NO.;	19
Filling Depth :	Increase ;	135	Times	Decrease ;	115	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	16	RPM	Capacity :	101760	Tablets/hour
Feeder : Status ;	Auto		Speed ;	30	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.20	mm	Pre Thickness ;	2.21	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.42	mm	Main Thickness ;	1.42	mm
Filling Depth :	7.54	mm	Current Cam :	Cam C	
Main Air pressure :	0.755	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	9	Min			
Lower Punch Remain Time (S2):	15	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.31	kN		
	Max ;	0.34	kN	Max Punch ;	46
Lower Punch :	Average ;	0.03	kN		
	Max ;	0.04	kN	Max Punch ;	50
Ejection Force :	Average ;	0.17	kN		
	Max ;	0.28	kN	Max Punch ;	27

Tablet Data (N/A)

Total Counter :	936688	Tablets			
A.W.C Counter :	926831	Tablets			
HEP :	211 (0.0%)	Tablets	LEP :	2 (0.0%)	Tablets
GOOD :	926618 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU 400 MG STIR1B00
User ID :	rp98927	Batch NO. :	IRM2507840
Print Interval :	50000 Tablets	Running Time :	08 Hour 40 Min 01 Sec
Total Counter :	936688	Total Running Time :	1577 Hour 16 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	176	%	Manual ;	16	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		1000000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		25	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	19.82	kN	No		
HEP :	20.0 %	18.30	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	15.55	kN	Yes 15	Times	
Ref :		15.25	kN			
LCP :	2.0 %	14.94	kN	Yes 15	Times	
LEP :	20.0 %	12.20	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	10.67	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	1.75	kN	Min :	1.53	kN	Punch NO.;	16
		5.40	%	Max :	2.03	kN	Punch NO.;	50
Mean Main Pressure :		15.14	kN	Min :	13.67	kN	Punch NO.;	48
	SD :	5.10	%	Max :	17.41	kN	Punch NO.;	37
Filling Depth :	Increase ;	45	Times	Decrease ;	55	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	16	RPM	Capacity :	101760	Tablets/hour
Feeder : Status ;	Auto		Speed ;	28	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.20	mm	Pre Thickness ;	2.21	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.45	mm	Main Thickness ;	1.45	mm
Filling Depth :	7.62	mm	Current Cam :	Cam C	
Main Air pressure :	0.755	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	9	Min			
Lower Punch Remain Time (S2):	15	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.30	kN		
	Max ;	0.34	kN	Max Punch ;	46
Lower Punch :	Average ;	0.03	kN		
	Max ;	0.04	kN	Max Punch ;	50
Ejection Force :	Average ;	0.17	kN		
	Max ;	0.28	kN	Max Punch ;	27

Tablet Data (N/A)

Total Counter :	936688	Tablets			
A.W.C Counter :	926831	Tablets			
HEP :	211 (0.0%)	Tablets	LEP :	2 (0.0%)	Tablets
GOOD :	926618 (100.0%)	Tablets			